

Multi-Tool

to fit 35mm exit shaft (Micro-perforating/Kiss-cutting; option1)

Stock Code: **MT- 02 OPTION 1**

Shaft Size: **35mm Exit Shaft**
Outer Diameter: **59.4mm**

SETTINGS



Additional Information

Compatible on:

SM 50/2
SM 54/4
SM 74/4
FA 50
FA 54
FA 74

Contents of Package

1x Male Blade Holder (MT-BH-GUK/35):
used to hold the perforating/slitting blade whilst material is fed through

2 x Female Nylon Sleeve Holders (CP-AP NSH-GUK/35):
used to secure nylon perforating and kiss-cutting process

1x Black Nylon Sleeve (CP-NY/SL-GUK):
used on light weight stocks (65-250/ 280gsm), to allow sufficient blade pressure onto material (for perforating and kiss-cutting only)

1x Blue Nylon Sleeve (CP-NY/SL-GUK-B):
used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

Kiss-Cutting Blade (CK-GUK-02):
(59.65mm Outer Diameter **optional**) used for kiss-cutting applications

2 x Black Gripper Bands (M-15):
used to feed and support material through device

Perforating Blades:

17 TPI (**MPB-17-GUK**) (250/280-350 gsm)
Blue Nylon Sleeve

17 TPI (**MPB-17-GUK**) (170-250/280 gsm)
Black Nylon Sleeve

25 TPI (**MPB-25-GUK**) (100-170 gsm)
Black Nylon Sleeve

52 TPI (**MPB-52-GUK**) (65-100 gsm)
Black Nylon Sleeve

12 TPI (**MPB-12-GUK**) (optional)



Tech 155 (Blade Holder) Tech 274 (Nylon Sleeve Holder)