

Multi-Tool

to fit 30mm exit shaft (Micro-perforating/Kiss-cutting; option1)

Stock Code: **MT- 04 OPTION 1**

Shaft Size: **30mm Exit Shaft**
Outer Diameter: **50mm**

SETTINGS



Additional Information

Compatible on:

Contents of Package

1x Male Blade Holder (MT-BH/04-30):
used to hold the perforating/slitting blade whilst material is fed through

2 x Female Nylon Sleeve Holders (CP-AP-NSH-30):
used to secure nylon perforating and kiss-cutting process

1x Black Nylon Sleeve (CP-NY/SL-30):
used on light weight stocks (65-250/ 280gsm), to allow sufficient blade pressure onto material (for perforating and kiss-cutting only)

1x Blue Nylon Sleeve (CP-NY/SL-30-B):
used on heavier stocks (250-280gsm upwards), allowing sufficient blade pressure onto material

Kiss-Cutting Blade (CK-30-02):
(50.35mm Outer Diameter **optional**) used for kiss-cutting applications

Perforating Blades:

- 17 TPI (**MPB-17/30mm**) (250/280-350 gsm) **Blue Nylon Sleeve**
- 17 TPI (**MPB-17/30mm**) (170-250/280 gsm) **Black Nylon Sleeve**
- 25 TPI (**MPB-25/30mm**) (100-170 gsm) **Black Nylon Sleeve**
- 52 TPI (**MPB-52/30mm**) (65-100 gsm) **Black Nylon Sleeve**

- 12 TPI (**MPB-12/25mm**) (optional)
- 72 TPI (**MPB-72/25mm**) (optional)

2 x Black Gripper Bands (M-51):
Used to feed and support material through device



Tech 119 (Blade Holder) Tech 273 (Nylon Sleeve Holder)