

# **Tubular Locksets**



(Version: 2015.6)

# RA/SE/GT/GS/LA/SF TRIM

UNISON HARDWARE, INC.



## TABLE OF CONTENTS

How to order	Page 1
Roses and Plates Escutcheons	Page 2
Lever Designs and Finishes	Page 3
Tubular Latch Set	Page 4
Tubular Entry Set	Page 5
Tubular Latch	Page 6-7
Privacy Bolt	Page 8
Deadbolt & Rim Cylinders	Page 9
Exploded Diagram	Page10-14
Care and Maintenance	Page 15
Product Warranty	Page 16

Disclaimer: All information in this catalog has been deemed accurate as of the date of printing. We are continuously improving and expanding our line in an effort to offer our clients the finest quality products and services. Therefore, Unison Hardware, Inc. reserves the right to alter this information or correct printing errors at any time.

®

#### STANDARD STOCK ITEM:

How to Order

For leversets using the same interior and exterior lever and finish combination:

## Product Identification **SF 105 L61-32D-LH**

	<b>Finish:</b> 32D = Satin Stainless Str 32 = Polished Stainless S SP = Two Tone Satin and 10B = Oil Rubbed Bronz	Steel d Polished Stainless Steel
RA Rose SE Rose GT Rose GS Rose	Lever: 101 Cologne 102 Munich 103 Oslo 104 Brussels 105 Frankfurt 106 Copenhagen 107 Stockholm 108 Vienna 109 Stuttgart 210 Air-stream 211 Breeze 213 Cabernet 214 Champagne 217 Horizon 221 Aurora 223 Phoenix 225 Waterfall 226 Summer 227 Stratus 243 Sunrise 244 Twilight 251 Sequoia 311 Crest 344 Ecco	Function:     Tubular Latch     L61 = Tubular Latch, Passage with TL2 Latch, 2-3/8" Backset     L65 = Tubular Latch, Privacy with TL2 Latch, 2-3/8" Backset     L65 = Tubular Latch, Privacy with TL2 Latch, 2-3/8" Backset     L66 = Tubular Latch, Passage with TL2 Latch, 2-3/8" Backset     L71 = Tubular Latch, Passage with TL2 Latch, 2-3/4"Backset     L72 = Tubular Latch, Passage with TL2 Latch, 2-3/4"Backset     L75 = Tubular Latch, Passage with TL2 Latch, 2-3/4" Backset     L76 = Tubular Latch, Passage with TL2 Latch, 2-3/4" Backset     L76 = Tubular Latch, Passage with TL2 Latch, 2-3/4" Backset     L76 = Tubular Latch, Passage with TL2 Latch, 2-3/4" Backset     L66 = Tubular Latch, Passage with TL4 Latch, 2-3/8" Backset     L461 = Tubular Latch, Passage with TL4 Latch, 2-3/8" Backset     L462 = Tubular Latch, Passage with TL4 Latch, 2-3/8" Backset     L465 = Tubular Latch, Passage with TL4 Latch, 2-3/8" Backset     L465 = Tubular Latch, Passage with TL4 Latch, 2-3/8" Backset     L475 = Tubular Latch, Passage with TL4 Latch, 2-3/4" Backset     L475 = Tubular Latch, Passage with TL4 Latch, 2-3/4" Backset     L475 = Tubular Latch, Passage with TL4 Latch, 2-3/4" Backset     L475 = Tubular Latch, Passage with TL4 Latch, 2-3/4" Backset     L476 = Tubular Latch, Passage with TL4 Latch, 2-3/4" Backset     L476 = Tubular Latch, Passage with T
LA Plate SF Plate	345 Tokyo 346 Osaka 351 Toronto 379 Arctic (GT/GS) 380 Polaris (RA/SE/LA/SF)	C64 = Combo Deadbolt and TL2 Latch, 2-3/8" Backset, Double Cylinder C74 = Combo Deadbolt and TL2 Latch, 2-3/4" Backset, Double Cylinder C464 = Combo Deadbolt and TL4 Latch, 2-3/8" Backset, Double Cylinder C474 = Combo Deadbolt and TL4 Latch, 2-3/4" Backset, Double Cylinder EDP = Dummy Entry with Dummy Cylinder





### **Roses and Plates Escutcheons**

®





#### Lever Designs and Finishes



102 Munich (32, 32D)

109 Stuttgart (32, 32D)

244 Twilight (32, 32D)

346 Osaka (32, 32D)

\*SP is a two-tone stainless steel finish: satin (32D) finish on lever grip, polished (32) finish on lever neck and roses. 379 Arctic knob are available for GT/GS small rosette and BP/MU plates. 380 Polaris knobs are available for RA/SE rosette, LA/SF plates and Entrance Handlesets.

Finish





· Satin Stainless Steel US32D/630

· Bright Polished Stainless Steel US32/629

· Two-tone Stainless Steel SP(Satin on Lever Grip; Polished on Lever Neck and Roses)



· Oil Rubbed Bronze on Stainless Steel 10B/613



#### Tubular Latch Set



#### Application

For residential interior doors with passage, privacy, or dummy application.

#### Material

Stainless Steel Levers and Escutcheons

#### Specification

- Door Thickness: 1-3/8" (35mm) to 1-3/4" (44mm) Thick Door Kits Available
- · Latch Backset: 2-3/8" (60mm) standard 2-3/4" (70mm) optional
- $\cdot$  Latch: Available for both TL2 and TL4 Latch
- Handing:

Field reversible latch for passage and privacy function. Specify handing for half passage and passage w/ privacy bolt function

- · Hub and Spindle: 5/16 (8mm) square
- · Latch Faceplate: 1"x2-1/4" standard square corner
- · Latch Strike:

Full lip strike and T-strike with square corners. Radius corner faceplate and strike, or ASA Strike also available. Order separately.

· Leverset Thru-bolts: 2 EA M4x35mm

#### **Door Preparation**





**GT** Series Prep

#### Standard Prep (\*except for GT)



LA/ SF Privacy Set Prep

Please go to: <u>www.inoxproducts.com/resources</u> for the latest door preparation templates and installation instructions.



#### **Functions:** Non-Keyed Lock



Passage (L61/L71/L461/L471) Both levers always unlocked.

#### Privacy (L62/L72/L462/L472)

Push privacy pin from inside to lock door. Unlock latch by turning inside lever or by emergency release from hole on outside rose cover.

d	1	
ן ר	Π	
Ц	닏	
L	μ	

Full Dummy - LA,SF MDP (Higher Lever Position) Both levers are inactive.

Half Dummy Left (DL) or Half Dummy Right (DR) Left or Right levers are always inactive. Optional working dummies available by specifying "WORKING".

#### Half Passage (L65/L75/L465/L475)

Outside lever always unlocked, inside dummy rose. Used on pantry/closet without space for inside lever. \*Do NOT use this function on pantry/or closet that could lock a person or pet inside.







GT Privacy Set

RA w/ GR Privacy Set SF Privacy Set



**Passage with Privacy Bolt- RA, SE, GT, GS** Combination of a passage set with an additional Privacy Bolt ordered separately. Please See Page 8 for Privacy Bolt details.



Passage with Privacy Bolt- LA,SF (L66/L76/L466/L476)

Combination of a passage set with privacy bolt.

Version: 2015.6



#### Tubular Entry Set





#### Application

For residential entry doors application.

#### Material

Stainless Steel Levers and Escutcheons

#### Finish



· Satin Stainless Steel US32D/630

Bright Polished Stainless Steel
US32/629

• Two-tone Stainless Steel SP( Satin on Lever Grip; Polished on Lever Neck and Roses)

· Oil Rubbed Bronze on Stainless Steel 10B/613

\*See page 3 for finish availability.

#### Specification

- Door Thickness: 1-3/8" (35mm) to 1-3/4" (44mm) Thick Door Kits Available
- · Backset: 2-3/8" (60mm) standard 2-3/4" (70mm) optional
- · Center Distance: 5-1/2" (140mm)
- Handing: Specify handing for all functions. Latchbolt is field reversible.
- · Hub and Spindle: 5/16 (8mm) square
- · Latch Faceplate: 1"x2-1/4" standard square corner
- · Latch Strike:
- Full lip strike and T-strike with square corners. Radius corner faceplate and strike, or ASA Strike also available. Order separately.
- Schlage C Keyway 5-pin Cylinder, 2 keys included. Keying service available.
- · Leverset Thru-bolts: M4x35mm
- Deadbolt Thru-bolts: 2 EA M5x50mm for Single Cylinder 2 EA M5x70mm for Double Cylinder

#### **Functions**



**Entry w/ Single Cylinder (C63/C73/C463/C473)** Deadbolt is locked or unlocked by key or thumb-turn inside. When deadbolt is unlocked, both levers operate latch like a passage set. Deadbolt and latch are not interconnected.





**Dummy Entry (EDP) (Lower Lever Position)** Both levers are inactive. Dummy cylinder is inactive.

**Dummy Pair (DP) (Lower Lever Position)** Both levers are inactive.

#### **Door Preparation**



Please go to: <u>www.inoxproducts.com/resources</u> for the latest door preparation templates and installation instructions.



#### **Tubular Latch**

TL2- Residential Grade





45 Degree Latch Retraction Backset: 2-3/8" (60mm), 2-3/4" (70mm) Function: Passage, Privacy, Dummy Faceplate: 1"x2-1/4"

Backset	Function	ltem No.
2-3/8" (60mm)	Passage	TL261
2-3/8" (60mm)	Privacy	TL262
2-3/4" (70mm)	Passage	TL271
2-3/4" (70mm)	Privacy	TL272
2-3/8" (60mm)	Dummy	TL260
2-3/4" (70mm)	Dummy	TL270

#### **Change Latch Bolt Direction For TL2 Latch**

TL2 Latch



Take out the latch and turn 180°



#### **Tubular Latch**

TL4 – Commercial Grade (BHMA/ANSI156.2 Grade 2)



28 Degree Latch Retraction Backset: 2-3/8" (60mm), 2-3/4" (70mm) Function: Passage, Privacy Faceplate: 1"x2-1/4"

Backset	Function	Item No.
2-3/8" (60mm)	Passage	TL461
2-3/8" (60mm)	Privacy	TL462
2-3/4" (70mm)	Passage	TL471
2-3/4" (70mm)	Privacy	TL472

#### **Change Latch Bolt Direction For TL4 Latch**

TL4 Latch 28 degree retraction latch



Determine door handing

for latch and remove INSIDE

washer (privacy pin side).

Change the latch direction 180° with the faceplate

attached to the latch body.

Note: Be sure to install the latch with faceplate

together.



Note: Make sure the center line on the back of the faceplate meets the center seam of the latch case.



Note: Make sure the latch has the Arrow facing up.



#### **Privacy Pin**

All privacy latches come with M4 Privacy Pin and Emergency Release Key

M4 Privacy Pin



#### **Emergency Release Key**



## Latch Bracket/ Stablizer

For 1-3/8" and 1-3/4" Door Thickness

TL2 Latch Bracket (For RA/SE/LA/SF) BRIX22F & BRIX22M



TL4 Latch Bracket (For RA/SE/LA/SF) BRIX40F & BRIX40M



#### Strikes

All latches come with both T-Strike and Full-lip Strike with square corners. Full-lip Strike with Radius Corner and ASA Strike can be ordered seperately.

Full-lip Strike LSR-D1 1-3/4"x2-1/4"



Full-lip Strike ¼" Corner LSR-D14 1-3/4"x2-1/4"



T- Strike LSR-T1 1-1/8" x 2-3/4" w/lip 1-1/2"x1/2"



ASA Strike (ANSI Standard) LSR-ASA 1-1/4"x4-7/8"

#### **Pre-Rose Lever Designs**

Certain lever designs have non-release rose cover where additional special allen wrench and hexagon bolts are provided. Designs include: 106 Copenhagen, 214 Champagne, 251 Sequoia, 344 Ecco, 379 Arctic, 380 Polaris, 243 Sunrise

Ways to install leverset with non-release rose cover





Jse a phillins screwdriver

Use allen wrench in between rose cover and under-construction.

Use allen wrench to go through rose cover center cut out

Use a phillips screwdriver to go through rose cover center cut out

\* keep the protective film on the lever while mounting the fixings





#### **Privacy Bolt**



- · Door Thickness: 1-3/8" (35mm) to 1-3/4" (44mm)
- · Backset: 2-3/8" (60mm) or 2-3/4" (70mm)

®

- · Privacy Bolt: 1/2" (12.7mm) throw
- · Privacy Bolt Spindle: 3/16" (5mm) square
- · Standard Faceplate: 1" x 2-1/4" Square Corners
- · Strike: 1" x 2-1/4" Square Corner

Backset	Item No.
2-3/8″	PB162
2-3/4″	PB172

#### Functions

1

	Privacy Deadbolt
	Deadbolt locked and unlocked by inside
	thumb-turn or outside emergency release

I I	
Item No.	Description
GT04PB62W	Privacy Bolt with GT Rose, 04 T-turn, 2-3/8" Backset, With Indicator
GT04PB72W	Privacy Bolt with GT Rose, 04 T-turn, 2-3/4" Backset, With Indicator
GT04PB62	Privacy Bolt with GT Rose, 04 T-turn, 2-3/8" Backset
GT04PB72	Privacy Bolt with GT Rose, 04 T-turn, 2-3/4"Backset
Item No.	Description
GS04PB62W	Privacy Bolt with GSRose, 04 T-turn, 2-3/8" Backset, With Indicator
GS04PB72W	Privacy Bolt with GS Rose, 04 T-turn, 2-3/4" Backset, With Indicator
GS04PB62	Privacy Bolt with GS Rose, 04 T-turn, 2-3/8" Backset
GS04PB72	Privacy Bolt with GS Rose, 04 T-turn, 2-3/4"Backset
Item No.	Description
GR04PB62	Privacy Bolt with GR Rose, 04 T-turn, 2-3/8" Backset
GR04PB72	Privacy Bolt with GR Rose, 04 T-turn, 2-3/4" Backset
SR04PB62	Privacy Bolt with SR Rose, 04 T-turn, 2-3/8" Backset
SR04PB72	Privacy Bolt with SR Rose, 04 T-turn, 2-3/4"Backset



#### **Rose Options with T-turn & Release**







GT Rose GT Rose T-Turn Side **Release only** 

GT Rose Release w/Indicator









GS Rose GS Rose **Release only** T-Turn Side

GS Rose Release w/Indicator









**GR** Rose **GR** Rose T-Turn Side **Release Side** 



SR Rose



SR Rose T-Turn Side

**Release Side** 





Please go to: www.inoxproducts.com/resources for the latest door preparation template and installation instructions.



R



Backset: 2-3/8" (60mm), 2-3/4" (70mm) Deadbolt: 1" (25mm) throw with anti-drill pin Function: Suitable for entry door or doors needing to be locked Faceplate: 2-1/4" x 1"

Cylinder & Keys: 5-pin Schlage C keyway cylinder with 2 keys

Backset	Item No.	
2-3/8″	BT160	
2-3/4″	BT170	

#### **Deadbolt Strike and Faceplate**

Deadbolt Faceplate

Deadbolt Strike w/ reinforcement plate and dustbox





BT1-FSP

LSR-BT1

#### **Rim Cylinders**

Schlage C Keyway, 5 Pin, with Tailpiece, 2 Keys. Standard Keyed Different (KD). Other Keying Services Available.





Dummy Cylinder CRA10D



Cylinder Escutcheon EC-R460COL

TT-04C

Thumb-turn



EC-S420COL





#### **Tubular Latch Set**



**Exploded Diagram** (RA Half Dummy)



- 1. Dummy Spindle
- 2. Wood Screws
- 3. Sub-rose
- 4. Lever
- 5. Rose Cover
- 6. Wood Screws
- 7. Set Screw for Lever

#### **Exploded Diagram** (RA Half Passage)



- 1. Inside Blind Rose Cover
- 2. Thru-bolts
- 3. Inside Sub-rose
- 4. Inside Latch Bracket
- 5. Tubular Latch-TL2 Passage 13. Tubular Latch Strike Screws 6. Spindle 8mm Square

7. Outside Latch Bracket

8. Outside Sub-rose

14. Tubular Latch Strike

12. Tubular Latch Faceplate Screws

15. Tubular Latch Dust Box

10. Outside Rose Cover

11. Set Screw for Lever

9. Outside Lever

16. Tubular Latch Faceplate



#### **Tubular Latch Set**



16. Privacy Pin





#### Tubular Latch Set





- 1. Inside Rose with Thumb-turn
- 2. Spindle Sleeve
- 3. Privacy Bolt
- 4. Spindle 5mm Square
- 5. Privacy Release Sub-rose
- 6. Privacy Rose Cover
- 7. Thru-Bolts
- 8. Privacy Bolt Dust Box
- 9. Privacy Bolt Strike
- 10. Privacy Bolt Strike Screws
- 11. Privacy Bolt Faceplate Screws
- 12. Faceplate of Privacy Bolt



- 1. Thumb-turn
- 2. Privacy Rose Cover
- 3. Wood Screws
- 4. Inside Less Cover
- 5. Privacy Bolt
- 6. Outside Sub Cover with release
- 7. Outside Rose Cover
- 8. Privacy Bolt Dust Box
- 9. Privacy Bolt Strike
- 10. Privacy Bolt Strike Screws
- 11. Privacy Bolt Faceplate Screws
- 12. Faceplate of Privacy Bolt
- 13. Thumb-turn Washer
- 14. Set Screw for Thumb-turn



#### Tubular Latch Set



- 1. Outside Lever
- 2. Bolt Sleeves
- 3. Outside Cover Plate
- 4. Outside Sub-plate
- 5. Latch Bracket
- 6. Inside Sub-plate
- 7. Thru-Bolts
- 8. Wood Screws
- 9. Inside Cover Plate
- 10. Tubular Latch Dust Box
- 11. Tubular Latch Strike
- 12. Tubular Latch Strike Screws
- 13. Tubular Latch Faceplate Screws
- 14. Tubular Latch Faceplate
- 15. Tubular Latch-TL2 Passage 16. Lever Spindle 8mm Square
- 17. Set Screw for Lever
- 17. Set Screw for

#### Exploded Diagram (LA Dummy)



- 1. Outside Lever
- 2. Outside Cover Plate
- 3. Outside Sub-plate
- 4. Inside Sub-plate
- 5. Wood Screws
- 6. Inside Cover Plate
- 7. Set Screw for Lever

#### Exploded Diagram (LA Privacy)



- 1. Inside Lever
- 2. Inside Cover Plate
- 3. Wood Screws
- 4. Inside Sub-plate
- 4. Inside Sub-pia

9. Bolt Sleeves

- 5. Latch Bracket
- 6. Lever Spindle 8mm Square
- 7. Outside Sub-plate 8. Outside Cover Plate
- 17. Thru-Bolts

10. Tubular Latch Dust Box

14. Tubular Latch Faceplate

15. Tubular Latch-TL2 Privacy

12. Tubular Latch Strike Screws

13. Tubular Latch Faceplate Screws

11. Tubular Latch Strike

16. Set Screw for Lever

18. Privacy Pin

#### **Exploded Diagram** (LA Passage with Privacy Bolt)



- 1. Outside Lever
- 2. Outside Cover Plate With Sub-rose
- 3. Privacy Bolt
- 4. Inside Lever
- 5. Inside Sub-plate
- 6. Thru-Bolts for Sub-plate
- 7. Inside Cover Plate
- 8. Thumb-turn Washer
- 9. Thumb-turn
- 10. Set Screw for Thumb-turn
- 11. Faceplate of Pricacy Bolt

- 12. Strike Screws
- 13. Privacy Bolt Strike
- 14. Privacy Bolt Dust box
- 15. Tubular Latch Dust Box
- 16. Tubular Latch Strike
- 17. Faceplate Screws
- 18. Faceplate of Tubular Latch
- 19. Tubular Latch-TL2 Passage
- 20. Latch Bracket
- 21. Lever Spindle 8mm Square
- 22. Set Screw for Lever



<u>(</u>5) <u>(</u>4)

#### **Tubular Entry Set**



- 1. Keys
- 2. Outside Rim Cylinder w/Tailpiece
- 3. Outside Cover Plate
- 4. Outside Cylinder
- Escutcheon
- 5. Outside Sub-plate
- 6. Lever Spindle 8mm Square
- 7. Deadbolt
- 8. Inside Sub-plate
- 9. Cylinder Thru-bolts
- 10. Inside Cover Plate
- 11. Thumb-turn Washer
- 12. Thumb-turn
- 13. Set Screw for Thumb-turn
- 14. Deadbolt Faceplate Screws

Exploded Diagram (LA Dummy Entry)

- 15. Deadbolt Strike Screws
- 16. Deadbolt Strike

- 17. Deadbolt Dust Box 18. Deadbolt Reinforcement
- **Plate Screws** 19. Deadbolt Reinforcement

- Screws
- 24. Tubular Latch Faceplate



2. Outside Rim Cylinder w/Tailpiece

(14

(15)

16

17

- 3. Outside Cover Plate
- 4. Outside Cylinder Escutcheon
- 5. Outside Sub-plate
- 6. Lever Spindle 8mm Square
- 7. Deadbolt
- 8. Inside Sub-plate
- 9. Inside Cover Plate
- 10. Inside Cylinder Escutcheon
- 11. Inside Rim Cylinder w/Tailpiece
- 12. Cylinder Thru-bolts

1. Outside Lever

2. Outside Cover Plate

3. Outside Sub-plate

4. Inside Sub-plate

- 13. Deadbolt Faceplate Screws
- 14. Deadbolt Strike Screws

-24 -25 26 -27 15. Deadbolt Strike

Exploded Diagram (LA Entry with Double Cylinder)

23

- 16. Deadbolt Dust Box
- 17. Deadbolt Reinforcement **Plate Screws**
- 18. Deadbolt Reinforcement Plate
- 19. Tubular Latch Dust Box
- 20. Tubular Latch Strike
- 21. Tubular Latch Strike Screws
- 22. Tubular Latch Faceplate Screws
- 23. Tubular Latch Faceplate
- 24. Tubular Latch-TL2 Passage
- 25. Latch Bracket
- 26. Set Screw for Lever
- 27. Outside Lever

#### Exploded Diagram (LA Dummy Pair)



- 5. Wood Screws 6. Inside Cover Plate
  - 7. Set Screw for Lever

- 2. Outside Blind Cylinder 3. Outside Cover Plate 4. Outside Cylinder Escutcheon
- 5. Outside Sub-plate

10

1. Outside Lever

6. Inside Sub-plate 7. Cylinder Thro-bolts 8. Wood Screws 9. Inside Cover Plate 10. Set Screw for Lever



- Plate 20. Tubular Latch Dust Box 21. Tubular Latch Strike
- 22. Tubular Latch Strike
- Screws
- 23. Tubular Latch Faceplate
- 25. Tubular Latch–TL2 Passage
- 26. Latch Bracket
- 27. Set Screw for Lever
- 28. Outside Lever

## Care and Maintenance

#### Lever and Knob Handles

On installations where the correct procedures have been carried out per the instructions, the lever handles will not require adjustment. However, all fixings should be checked for tightness annually. Any loose fixings should be adjusted. Badly fitted furniture can cause interference with the operation of the lock and at the same time, damage the surface of the furniture. INOX<sup>®</sup> snap-on rose covers should only be removed using proper tools. A screw driver blade should never be used as this can distort the rose cap out of alignment and scratch the surfaces of both product and door.

#### **Care of Finishes**

Today's environment exerts immense pressures on product material requirements. Products must withstand a diversification of atmospheric conditions, such as high pollution, marine locations, and high humidity climates. Additionally, products must be protected against cleaning agents/solutions and ideally the product should offer hypo-allergenic properties.

#### **Stainless Steel**

Stainless steel is renowned for the following two properties; resistance to corrosion and low maintenance requirements. Stainless steel corrosion resistance is attributable to the presence of a thin, durable film of passive, but stable, chromium oxide. Being inert, invisible, extremely adherent and self-repairing, this film provides an unrivalled protection for the steel; should the film be damaged or removed it will regenerate independently, provided that oxygen is present to allow the reaction to occur with the chromium content of the steel. Therefore you must ensure regular cleaning and maintenance, to restore the original surface appearance, prevent corrosion and maintain hygienic conditions.

#### **Cleaning Technique**

It is important to clean stainless steel regularly.

- Initially, wash down the surface using soapy water or a mild detergent.
- · Always thoroughly rinse the cleaning agent away with clean, warm water.
- To complete the cleaning procedure, dry/polish the item with a soft, dry cloth.

Note: Within aggressive conditions, such as offshore, marine and swimming pool environments, it is especially relevant to ensure that cleaning maintenance occurs regularly.

#### Discoloration

If spots appear on the surface it is not due to the stainless steel, but to impurities in the water, the air or to cleaning agents that have not been thoroughly removed from the surface.

· Spots can be avoided by careful cleaning.

• If discoloration or spots occur they can be removed by using special polishing agents for stainless steel or a light scouring cream.

· Again rinse thoroughly with clean water and polish with a soft, dry cloth.

#### What to Avoid!

- · Scouring powders
- Steel wool
- Strong abrasive materials

Note: Acid based cleaning solutions, except for hydrochloric acid, may be used on AISI 304 stainless steel as long as thoroughly rinsed with clean water afterwards. For further information on stainless steel, please contact your local INOX<sup>®</sup> distributor for the INOX<sup>®</sup> Stainless Steel Technical Details information sheet.

## **Product Warranty**

#### **Limited Lifetime Warranty**

Unison Hardware, Inc. warrants that its INOX<sup>®</sup> residential products shall be free from defects in material and workmanship for the life of the product, excluding components made of wood, leather or plastic. This warranty extends to the original purchaser and the first consumer owner only. If a product fails due to defects in material or workmanship during the warranty period we will replace it with the most nearly identical product which we sell at the time or refund the original purchase price. Unison Hardware, Inc. will not be liable for any labor charges or freight costs incurred in connection with repair or replacement of a product. Our sole and maximum liability for defective goods (Sold and manufactured by Unison Hardware, Inc.) shall never exceed the cost of the subject products.

#### This warranty does not cover:

- a. Damage resulting from negligence, misuse, abuse or accident occurring after installation
- b. Damage due to use outside normal architectural requirements
- c. Defects resulting from any modification or improper installations
- d. Improper torquing (tightening) during or after installation
- e. Improper door preparations
- f. Use of residential grade products in commercial applications (i.e. public building, restaurants, offices etc.)
- g. Products installed within three miles of the ocean
- h. Products installed in exterior application and/or exposed to the outdoor weather or elements

#### **Limited Lifetime Finish Warranty**

Unison Hardware, Inc. warrants its INOX<sup>®</sup> products made of stainless steel material against tarnishing. This warranty is extended to the original purchaser of INOX<sup>®</sup> products as long as the User occupies the residential premises on which the Products were originally installed. Not covered under this warranty are:

- a. Products which have been scratched or abraded
- b. Products which have been incorrectly installed or mistreated
- c. Products installed within three miles of water (ocean, lakes, rivers, etc.), harsh environments and/or commercial or industrial applications
- d. Products installed in exterior application and/or exposed to the outdoor weather or elements
- e. Finishes which are specifically designed to wear over time (i.e. Oil Rubbed Bronze finish)

UNISON HARDWARE, INC. MAKES NO OTHER WARRANTY, AND ALL IMPLIED WARRANTIES INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE LIMITED TO THE DURATION OF THE EXPRESSED WARRANTY PERIOD AS SET FORTH ABOVE. THE COMPANY'S MAXIMUM LIABILITY HEREUNDER IS LIMITED TO THE PURCHASE PRICE OF THE PRODUCT. IN NO EVENT SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, INDIRECT, INCIDENTAL OR SPECIAL DAMAGES OF ANY NATURE ARISING FROM THE SALE OR USE OF THIS PRODUCT, WHETHER IN CONTRACT, TORT, STRICT LIABILITY OR OTHERWISE.THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS AND MERCHANTABILITY. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF.





Please visit our website <u>www.inoxproducts.com</u> for more technical and new product information.



**Unison Hardware, Inc.** 6 Wayne Court, Sacramento, CA 95829, USA Tel: +1.916.388.1888 Fax: +1.916.388.8322 Email: info@unisonhardware.com