

PUMPER

BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Sober FR Chassis

CHASSIS

AXLE, FRONT, CUSTOM

18,000 Lb Dana Axle

AXLE, REAR

24,000 Lb Dana Axle

ENGINE

400 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

13" Extended Painted Steel

CAB

6010 Sober FR Cab

BODY

WATER TANK

725 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

30.75" FF RollUp Rear Compt

COMPT, PUMPER, LEFT SIDE

152" RollUp Full Height Front & Rear FDLER

COMPT, PUMPER, RIGHT SIDE

152" RollUp Full Height Front & Rear FDLER

FIRE SUPPRESSION

PUMPHOUSE

52" Control Zone Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Akron Educator Foam System

Foam Cell

25 Gallon Foam Cell, Not Reduced Water

Side View Labels:

- STORAGE COMPARTMENT FOR (2) BACKBOARDS (2' X 18" X 72")
- (1) WHELEN PIONEER L.E.D. SCENE LIGHT WITH PUSH UP POLE EACH SIDE
- (1) PIERCE REAR VIEW CAMERA EACH SIDE
- 116.00 (9'-8") APPROX O.A.H.
- 1/8" LIGHT SHIELD

Top View Labels:

- (1) WHELEN PIONEER L.E.D. VISOR LIGHT
- (3) WHELEN FREEDOM IV 21.50" L.E.D. LIGHTBARS
- RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
- (1) WHELEN M6 L.E.D. WARNING LIGHT
- (1) WHELEN M6 L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
- (2) WHELEN LIN3 L.E.D. WARNING LIGHTS
- 6.00" INLET WITH 5.00" PIPING
- (3) WHELEN M7 L.E.D. WARNING LIGHTS EACH SIDE
- (1) 1.50" OUTLET WITH 2.00" PIPING AND SWIVEL
- (2) FEDERAL ES1010C SPEAKERS WITH "EF" GRILLES
- (1) FEDERAL Q2B SIREN
- (2) GROVER AIR HORNS
- CENTER HOSE TRAY FOR 100' OF 1.75" HOSE

HOSEBED CAPACITY

BED 1
400' OF 3.00" D.J. POLY HOSE
BED 2
1000' OF 5.00" D.J. POLY HOSE
BED 3
200' OF 3.00" D.J. POLY HOSE

Bottom View Labels:

- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS EACH SIDE
- (1) WHELEN PSTANK2 L.E.D. WATER LEVEL INDICATOR LIGHT EACH SIDE
- (1) FRP L.E.D. LIGHT FOR DESIGNATED WALKING AREA
- 14.75 CLEAR 17.25
- 74.25 70.00
- 76.00
- 136.00
- 9.25 8.75 10.75 6.00
- 6.33
- 17.00
- 1/8" LIGHT SHIELD
- 61.00 30.00
- 57.50 24.00
- 64.75
- 31.50 2.25 27.13 47.50
- 3.00
- 3.25
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00 31.50 35.50 42.00 28.00 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
- 10.75
- 6.00
- 4.00
- 3.00
- 1.75
- 43.00
- 16.25
- 43.75
- 12.00
- 12.25
- 19.00
- 36.50
- 21.50
- 40.25
- 36.00
- 30.75
- 14.00
- 28.00
- 40.00
- 28.00
- 96.00
- 91.00
- 72.00
- 5'-7"
- DUO-SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING 585A
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- (2) ALUMINUM PIKE POLE TUBES
- PIERCE REAR VIEW CAMERA W/ GUARD
- (1) 3.00" OUTLET
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN L31HRN L.E.D. WARNING LIGHTS
- (2) WHELEN PIONEER L.E.D. SCENE LIGHTS
- (2) WHELEN 600 L.E.D. STOP/TAI LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN CAST3 BEZELS
- (2) WHELEN M7 L.E.D. WARNING LIGHTS
- AIR INLET/OUTLET W/ DISCONNECT FITTING
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT
- 8.00" NFPA MIN.
- 8.00" NFPA MIN.
- 2.00
- 52.00
- 1.50
- 66.00
- 31.50
- 35.50
- 42.00
- 28.00
- 16.00
- 181.50 WB
- 353.25 (34'-5.25") APPROX OAL
- 82.00
- 60.00
- 20.00
- 2.25
- 52.50
- 17.00
- 6.33
-