



ALUMINUM BODY MAXIMUM O.A.H. 148.00" MAXIMUM O.A.L. 380.00"

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. AIR INLET WITH KUSSMAUL AIR EJECT LOCATED IN DRIVER SIDE STEP WELL
2. AIR OUTLET WITH SHUT OFF VALVE LOCATED AT DRIVER SIDE PUMP PANEL
3. BATTERY CHARGER LOCATED IN COMPARTMENT-LS3
4. SUB-FEED CIRCUIT BREAKER PANEL IN COMPARTMENT-LS3
5. PULL STRAPS FOR DOORS IN COMPARTMENTS-LS1,LS2,LS3,RS2
6. ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF WITH SIDES IN COMPARTMENTS-LS1,LS3, RS1, RS3; TWO IN B1
7. ONE ADJUSTABLE TILT/SLIDE-OUT TRAY IN COMPARTMENT- LS2,LS3,RS3; TWO IN LS1
8. CIRCUIT BREAKER PANEL LOCATED IN COMPARTMENT-LS3
9. ONE HANNAY ECR1616-17-18 3-WIRE ELECTRIC REWIND CORD REEL WITH 200' OF 12/3 CABLE IN COMPARTMENT-B1

- FIRE RESEARCH FCABS1-M10 VISOR LIGHT
- (2) GROTE TRILLIANT 63J01 L.E.D. VISOR LIGHTS
- RETRACT HEATED/REMOTE MIRRORS WITH CONVEX SECTION
- (2) WHELEN LINZ6 L.E.D. WARNING LIGHTS
- (2) WHELEN 600 L.E.D. DIRECTIONAL LIGHTS
- NON-EXTENDED BUMPER
- (2) WHELEN LINZ6 L.E.D. WARNING LIGHTS EACH SIDE
- COLEMAN MACH 3 AIR CONDITIONER
- WHELEN JUSTICE 56.25" L.E.D. LIGHTBAR
- (2) HADLEY AIR HORNS
- (2) TOW ANCHORS
- WHELEN SA315 SPEAKER
- (2) 25 GALLON FOAM CELLS
- ONAN HDKAG 10KW DIESEL GENERATOR WITH ALUMINUM TREADPLATE COVER
- UNDER PUMP HEAT ENCLOSURE
- DOUBLE AIR BOTTLE COMPARTMENT WITH STAINLESS STEEL DOOR EACH SIDE
- WELDON 9186-8580-29 L.E.D. DIRECTIONAL/MARKER LIGHT EACH SIDE
- (2) SPEEDLAY HOSE BEDS FOR 200' OF 1.75" HOSE AND 2.00" PIPING
- RUNNING BOARD HOSE TRAY FOR 20' OF 5.00" SOFT SUCTION HOSE EACH SIDE
- 3.00" DELUGE OUTLET WITH TFT XG18 EXTEND-A-GUN FOR ELKHART STINGER 8297-25 MONITOR WITH ELKHART ST-194 STACKED TIPS AND 282-A SHAPER
- HUSKY 12 FOAM SYSTEM
- (3) FRP L.E.D. LIGHTS FOR DESIGNATED WALKWAY
- WHELEN M6 L.E.D. SCENE LIGHT EACH SIDE
- FIRE RESEARCH FC4530-M12 1000W FOCUS FLOOD LIGHT WITH EXTENDABLE POLE EACH SIDE
- DIESEL EXHAUST FLUID ACCESS WITH STAINLESS STEEL DOOR
- WHELEN M6 L.E.D. SCENE LIGHT EACH SIDE
- 0.25" PERMANENT HOSE BED DIVIDER
- (2) UNITY AG DECK LIGHTS
- (2) WHELEN MCFLED2 L.E.D. BEACON LIGHTS
- BACKBOARD STORAGE FOR (1) BACKBOARD (72.0" LX18.0" WX2.0")
- (2) 6.00" X10" HARD SUCTION HOSES WITH PAINTED TROUGH
- 2.50" HOSE BED OUTLET WITH 2.50" PIPING
- (2) WHELEN LINZ6 L.E.D. WARNING LIGHTS
- (2) ZIAMATIC SAC-44-E FOLDING WHEEL CHOCKS
- PIERCE CW144639CA1 BACKUP CAMERA
- (2) WHELEN M6 L.E.D. SCENE LIGHTS
- SWITCH FOR REAR SCENE LIGHTS
- (2) TRUCK-LITE 44 L.E.D. STOP/TAIL LIGHTS
- (2) TRUCK-LITE 44 L.E.D. DIRECTIONAL LIGHTS
- (2) TRUCK-LITE 44 L.E.D. BACKUP LIGHTS
- (2) WHELEN LINZ6 L.E.D. WARNING LIGHTS
- (2) 120V DUPLEX RECEPTACLES
- (2) 120V TWIST LOCK RECEPTACLES
- HOSEBED CAPACITIES
 - ① 1000' OF 5.00" D.J. POLY HOSE
 - ② 800' OF 3.00" D.J. POLY HOSE
- ZICO QUICK-LIFT ELECTRIC LADDER RACK TO CONTAIN THE FOLLOWING EQUIPMENT:
 - (1) 35' DUO-SAFETY 3-SEC 1225-A
 - (1) 14' DUO-SAFETY ROOF 775-A
 - (1) 10' DUO-SAFETY FOLDING 585-A
 - (1) 8' DUO-SAFETY PIKE POLE
 - (1) 6' DUO-SAFETY PIKE POLE

REV	DATE	BY	CH	SABER FR
1	11FEB20	KLE	PJP	PIERCE
2	14JAN20	KLE	PJP	MODEL

		JOB NO. 34536	
		SCALE 1:24	DATE
CHASSIS DATA TITLE 1250-D-500P W/(2) 25 GAL. FOAM CELLS,DELUGE 161" PUMPER RESCUE BODY,ZICO LADDER RACK,GENERATOR MAKE PIERCE FOR UNITED STATES AIR FORCE-GWANG JU AB KOREA PIERCE DIRECT		DRAWN BY KLE	07NOV19
DWG NO. 34536AD		CHECKED BY NPE	13NOV19
		SHEET SIZE D	SHEET NO. 1 OF 1