



ALUMINUM BODY MAXIMUM O.A.H. 154.00" MAXIMUM O.A.L. 380.00"

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. AIR INLET WITH KUSSMAUL AIR EJECT LOCATED IN DRIVER SIDE STEP WELL
2. AIR OUTLET WITH SHUT OFF VALVE LOCATED AT DRIVER SIDE PUMP PANEL
3. BATTERY CHARGER LOCATED IN COMPARTMENT LS3 HIGH ON THE LEFT WALL
4. PULL STRAPS FOR DOORS IN COMPARTMENTS LS1, LS2, LS3, RS1, RS2, AND RS3
5. ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF WITH SIDES IN COMPARTMENTS LS1, LS3, RS1, AND RS3, TWO IN RS1
6. ONE ADJUSTABLE TILT/SLIDE-OUT TRAY IN COMPARTMENTS LS2, LS3, AND RS3; TWO IN LS1
7. CIRCUIT BREAKER PANEL LOCATED IN COMPARTMENT LS3
8. ONE HANNAY ECR1616-17-18 3-WIRE ELECTRIC REWIND CORD REEL WITH 200' OF 12/3 CABLE IN COMPARTMENT B1

REV	DATE	BY	CH	CHASSIS DATA	TITLE
14MAY20	KLE	PJP	MAKE	1250-D-500P W/(2) 25 GAL. FOAM CELLS, DELUGE	
17MAR20	KLE	PJP	PIERCE	152" PUMPER RESCUE BODY, HYDRAULIC LADDER RACK	
22JAN20	KLE	NPE	MODEL	UNITED STATES AIR FORCE-USAF NELLIS AFB	
			SABER FR	PIERCE DIRECT	
			STEP FRAME		

		JOB NO.	34682
		SCALE	DATE
1:24		DRAWN BY	KLE
		CHECKED BY	NPE
		SHEET SIZE	SHEET NO.
		D	1 OF 1

34682AD

- HOSEBED CAPACITIES**
- 1 OPEN BED
 - 2 1000' OF 5.00" D.J. POLY HOSE
 - 3 800' OF 3.00" D.J. POLY HOSE

- HYDRAULIC LADDER RACK TO CONTAIN THE FOLLOWING EQUIPMENT:**
- (1) 35' DUO-SAFETY 3-SEC. 1225-A
 - (1) 14' DUO-SAFETY ROOF 775-A
 - (1) 10' DUO-SAFETY FOLDING SBS-A
 - (1) 8' DUO-SAFETY PIKE POLE
 - (1) 6' DUO-SAFETY PIKE POLE
 - (2) ALUMINUM PIKE POLE TUBES

- (2) 120V DUPLEX RECEPTACLES
 (2) 120V TWIST LOCK RECEPTACLES