



ALUMINUM BODY MAXIMUM O.A.H. 126.00" SIDE ROLL & FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 5/STL SCUFFPLATE ON EACH CAB DOOR JAMB
- BATTERY CHARGER ON THE CEILING OF RS2
- PULL STRAP ON DOOR IN COMPARTMENT LS2 AND RS2
- 5/STL SCUFFPLATE ON BOTTOM EDGE OF DOOR FRAMING OF ALL COMPARTMENTS EXCEPT B1
- 5/STL SCUFFPLATE INTERIOR OF DOOR IN EACH COMPARTMENT DOOR
- TWO SPECIAL WIDTH/DEPTH ADJUSTABLE SHELVES IN COMPARTMENT LS3
- ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF IN COMPARTMENT LS2, LS3, RS1, RS2 TWO IN LS1, THREE IN RS3
- ONE 0.25" THICK FIXED FULL WIDTH/DEPTH FIXED SHELF IN RS1
- ONE ADJUSTABLE MAX WIDTH AND DEPTH TRAY IN LS1
- TWO ADJUSTABLE LOW SIDE SPECIAL HEIGHT TRAYS IN B1
- ONE FLOOR MOUNTED SIDE-OUT TRAY WITH SIDE SLIDES/LOW/SPECIAL SIDES IN B1
- ONE POLY OPEN FRONT RETAINING TRAY SHIPPED LOOSE
- BRUSHED S/S ON THE FLOOR B1
- PARTITION BETWEEN LS1/B1 AND RS1/B1
- ONE VERTICAL PARTITION IN LS3
- RESPOND READY STORAGE W/ 4 DRAWERS IN LS4
- VENTILATION SYSTEM WITH TIMER IN RS3
- STORAGE BIN FOR THREE AIR BOTTLES IN THE BOTTOM OF RS3
- AIR INLET W/ DISCONNECT COUPLING IN D.S. STEP WELL
- AIR OUTLET WITH SHUT-OFF VALVE IN D.S. STEP WELL
- STORAGE BACK FOR ONE EXTINGUISHER IN RS4
- ONE 120V NEMA DUPLEX RECEPTACLE IN LS3 AND B1
- SUB FEED BREAKER BOX IN RS3

REV	DATE	BY	CH	VELOCITY
02DEC20	LST	GKH		
22OCT20	LST	GKH		
20MAY20	LST	WKL		

		JOB NO.	34956
		SCALE	1:24
TITLE 1500-D-500 GAL POLY, 152" BODY, FULL HEIGHT FRONT & REAR BOTH SIDES, FDLER, HLR, GENERATOR FOR THURSTON CO. FIRE DISTRICT #3, LACEY LACEY, WASHINGTON	DWG NO. 34956AD	DRAWN BY	LST
		CHECKED BY	WKL
		SHEET SIZE	D
		SHEET NO.	1 OF 1