



- HOSEBED CAPACITIES**
- ① 250' OF 2.50" D.J. POLY HOSE
 - ② 250' OF 2.50" D.J. POLY HOSE
 - ③ 400' OF 2.50" D.J. POLY HOSE
 - ④ 400' OF 2.50" D.J. POLY HOSE
 - ⑤ 1500' OF 5.00" D.J. POLY HOSE

- LADDER BRACKETS TO CONTAIN THE FOLLOWING EQUIPMENT:**
- (1) 24" DUO-SAFETY 2-SEC 900-A
 - (1) 14" DUO-SAFETY ROOF 775-DR
 - (1) 10" DUO-SAFETY FOLDING 585-A
 - (1) 8" FHU RH-8 PIKE POLE
 - (1) 6" FHU RH-6 PIKE POLE
 - (2) ALUMINUM PIKE POLE TUBES

ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. ONSPOT AUTOMATIC TIRE CHAINS
- 2. AIR INLET/OUTLET WITH DISCONNECT FITTING ON D.S. PUMP PANEL
- 3. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- 4. S/STL SCUFFPLATES AT HANDRAILS
- 5. DRIP PAN GUARD FOR ROLL-UP DOOR LOCATED IN COMPARTMENT B1
- 6. ONE FULL WIDTH ADJUSTABLE SHELF LOCATED IN COMPARTMENTS L51, TWO IN L53
- 7. ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENTS L53, B1
- 8. PEGBOARD ON BACK WALL OF COMPARTMENT L52

REV	DATE	BY	CH	ENFORCER
▽	21SEP20	JUS	CSH	CHASSIS DATA
▽	15SEP20	JWO	CSH	MAKE
▽	19AUG20	JWO	CSH	PIERCE
▽	29MAY20	JWO	KOU	MODEL

		JOB NO.	35067
		SCALE	DATE
TITLE	1500-D-1040P, 1000G WATER W/40G FOAM, 152" BODY LS FH, RS LOW, (2)CROSSLAYS, REEL, DELUGE, HUSKY 3		
FOR	CITY OF LYNCHBURG LYNCHBURG, VIRGINIA		
DWG NO.	35067AD		
	D	SHEET NO.	1 OF 1