



HOSEBED CAPACITIES

①	- 200' OF 1.75" HOSE
②	- 300' OF 2.50" HOSE
③	- 700' OF 3.00" HOSE
④	- 950' OF 5.00" HOSE

ALUMINUM BODY MAXIMUM O.A.H. 113" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- AIR INLET WITH DISCONNECT COUPLING LOCATED IN DRIVER'S SIDE STEP WELL
- ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- VOGEL LUBE SYSTEM PUMP LOCATED PER SHOP ORDER
- BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- ONE ADJUSTABLE FULL WIDTH/DEPTH SHELF IN COMPARTMENT LS2, LS3, RS1 & B1, TWO IN LS1
- ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT LS3
- ONE SMOOTH ALUMINUM TOOLBOARD W/ TRACK ON REAR WALL OF COMPARTMENT LS3
- ONE SMOOTH ALUMINUM TOOLBOARD WITH NO HOLES ADDED TO SLIDE-OUT TRAY IN COMPARTMENT LS3
- ONE ALUMINUM TOOLBOARD ON BACK WALL OF COMPARTMENT RS2

REV	DATE	BY	CH	ENFORCER
130CT20	COL	SMA	MAKE	CHASSIS DATA
10SEP20	MMF	SMA	PIERCE	FOR
12AUG20	COL	SMA	MODEL	DWG NO.

		JOB NO.	35165
		SCALE	1:24
TITLE 2000-D-500P 140" PUMPER BODY, (2)CROSSLAYS, DELUGE BOOSTER REEL, LADDERS ON PASSENGERS SIDE SHEET		DRAWN BY	COL
		CHECKED BY	NPE
FOR UNIFIED GOVERNMENT OF WYANDOTTE COUNTY KANSAS CITY, KANSAS		DATE	04MAY20
		SHEET SIZE	D
DWG NO. 35165AD		SHEET NO.	1 OF 1