



ALUMINUM BODY MAXIMUM O.A.H. 141.00" (11'-9.00")

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT THE REAR
- BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- SIX ADJUSTABLE FULL WIDTH/FULL DEPTH SHELVES LOCATED IN COMPARTMENTS PER SHOP ORDER
- ONE L-SHAPED ADJUSTABLE SHELF LOCATED IN COMPARTMENT LS1
- TEN ADJUSTABLE FULL WIDTH/FULL DEPTH LOW/SPECIAL SIDE HEIGHT SHELVES LOCATED IN COMPARTMENTS PER SHOP ORDER
- TWO ADJUSTABLE FULL WIDTH/FULL DEPTH LOW/SPECIAL SIDE HEIGHT SHELVES LOCATED IN TRANSVERSE COMPARTMENT L56-R56
- ONE FLOOR MOUNTED REMOVABLE SLIDE-OUT TRAY IN COMPARTMENT L53
- ONE VERTICAL PARTITION (SPECIAL HEIGHT) IN COMPARTMENT R54
- PIKE POLE STORAGE RACK IN TRANSVERSE COMPARTMENT L56-R56
- CIRCUIT BREAKER PANEL LOCATED IN COMPARTMENT L56
- GENERATOR METER PANEL LOCATED IN COMPARTMENT L56
- CARGO AREA LIGHTS LOCATED PER SHOP ORDER
- ONE 120V DUPLEX RECEPTACLE IN CAB PER SHOP ORDER
- ONE 120V DUPLEX RECEPTACLE IN COMPARTMENT R53
- STABILIZERS MODIFIED FOR 18" GROUND PENETRATION
- L.E.D. LIGHTING ON AERIAL LADDER SECTIONS
- 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNTABLE
- LIFTING EYE ROPE RESCUE ATTACHMENT AT AERIAL TIP
- TRIDENT FOLDING STEPS ON AERIAL DEVICE
- 1500 GPM HIGH FLOW WATERWAY
- 7.00" LIMITED RETRACTION REQUIRED
- 3.00" RAISED PEDESTAL

		JOB NO.	35167
		SCALE	DATE
CHASSIS DATA TITLE MAKE PIERCE MODEL VELOCITY	FOR CITY OF COLORADO SPRINGS COLORADO SPRINGS, COLORADO	107' AERIAL ASCENDANT LADDER AND BODY ASSEMBLY NO PUMP/NO TANK	12AUG20
		CHECKED BY SMA	12AUG20
DWG NO.	35167AD	SHEET SIZE	SHEET NO.
		D	1 OF 1