



BODY 110' Single Axle Platform Aluminum Body	WATER TANK 500 Gallon Poly Water Tank
COMPT, LEFT SIDE FRONT Full Height RollUp Forward	Foam System Husky 3 Single Agent Foam System
COMPT, LEFT SIDE REAR Full Height RollUp Rearward	Foam Cell 20 Gallon Foam Cell, Non-Reducing Water
COMPT, RIGHT SIDE FRONT Full Height RollUp Forward	
COMPT, RIGHT SIDE REAR Full Height RollUp Rearward	

CHASSIS Enforcer Chassis 450 HP Cummins L9 Engine	CAB 7010 Notched Enforcer Cab 19" Extended Stainless Steel	AXLE, FRONT, CUSTOM 24,000 Lb TAK-4 Axle AXLE, REAR 33,500 Lb Meritor Axle	TRANSMISSION Allison 5th Gen, 3000 EV5 P	PUMPHOUSE 52" Control Zone Side Mount PUMP 2000 GPM Waterous CSU	CROSSLAYS, 1.50" (2) 1.50" Standard Capacity CROSSLAYS, 2.50" (1) 2.50" Standard Capacity	SPEEDLAYS Speedlays Not Required GENERATOR Generator Not Required
--	---	---	--	--	--	--

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONE 1.50" OUTLET WITH 2.00" PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY
- SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED IN THE DRIVER SIDE STEPWELL
- AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
- BATTERY CHARGER LOCATED BEHIND DRIVERS SEAT
- BATTERY CHARGE INDICATOR LOCATED IN THE DRIVER SIDE STEPWELL
- NINE ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER
- ONE SWING-OUT ALUMINUM TOOL BOARD IN COMPARTMENT PER SHOP ORDER
- FOUR FLOOR MOUNTED SLIDE-OUT TRAYS IN COMPARTMENTS PER SHOP ORDER
- TWO 120V 4-PLACE DUPLEX RECEPTACLES IN COMPARTMENTS PER SHOP ORDER
- NON-RAISED AERIAL PEDESTAL
- AERIAL WIRELESS REMOTE CONTROL
- 12, 1250 GPM HIGH FLOW WATERWAY
- NO LIMITED RETRACTION

Pierce MANUFACTURING INC.		JOB NO.	35308
		SCALE	DATE
		1:24	30APR20
		DRAWN BY	TKA
		CHECKED BY	THS
		SHEET SIZE	SHEET NO.
		D	1 OF 1

CHASSIS DATA
 TITLE: 110' ASCENDANT AERIAL LADDER AND BODY ASSEMBLY
 MAKE: PIERCE
 FOR: CITY OF ARTESIA FIRE DEPARTMENT
 ARTESIA, NEW MEXICO
 DWG NO.: 35308AD