



ALUMINUM BODY

MAXIMUM O.A.H. 140.00"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED IN CREW CAB SEAT RISER
- BATTERY CHARGER INDICATOR LOCATED AT DRIVER'S SIDE STEP AREA
- AIR INLET WITH DISCONNECT COUPLING LOCATED AT DRIVER'S SIDE STEP AREA
- AIR OUTLET WITH SHUT-OFF VALVE LOCATED AT DRIVER'S SIDE STEP AREA
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- JUMPER STUDS AT DRIVER'S SIDE CAB STEP
- ELASTIC PULL STRAP FOR EACH ROLL-UP DOOR
- DRIP PAN GUARD FOR EACH ROLL-UP DOOR
- SIX ADJUSTABLE FULL WIDTH/FULL DEPTH SHELVES IN COMPARTMENTS PER SHOP ORDER
- ONE ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENT PER SHOP ORDER
- THREE FULL WIDTH/DEPTH FLOOR MOUNTED SLIDE-OUT TRAYS WITH SIDE SLIDES IN COMPARTMENTS PER SHOP ORDER
- ONE ALUMINUM SWING-OUT TOOLBOARD WITH PAC TRAC IN COMPARTMENT PER SHOP ORDER
- PAC TRAC ON THE REAR WALL OF COMPARTMENTS PER SHOP ORDER
- TWO 1.00" RETAINING LIPS IN COMPARTMENTS PER SHOP ORDER
- TRIDENT FOLDING STEPS ON AERIAL DEVICE
- STABILIZERS MODIFIED FOR 18" GROUND PENETRATION
- L.E.D. LIGHTING ON AERIAL LADDER SECTIONS
- 120V POWER TO AERIAL TIP
- 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNABLE
- CIRCUIT BREAKER PANEL WITH COVER LOCATED IN COMPARTMENT PER SHOP ORDER
- AIR HORN CONTROL AT AERIAL TURNABLE
- 1500 GPM HIGH FLOW WATERWAY
- 14.00" LIMITED RETRACTION ON AERIAL FLY SECTION
- LIFTING EYE ROPE RESCUE ATTACHMENT AT AERIAL TIP
- AERIAL PEDESTAL RAISED 3.00"
- HANNAY ALUMINUM BOOSTER REEL MODEL SBEF20-30-31 WITH 150' OF 1.00 HOSE AND 1.50" PIPING LOCATED ABOVE PUMP WITH THREE ROLLER ASSEMBLIES

		JOB NO.	35328-01-02
		SCALE	DATE
CHASSIS DATA	TITLE	107' ASCENDANT AERIAL LADDER AND BODY ASSEMBLY	
	FOR	520 GALLON TANK, 500 GAL. WATER/20 GAL. FOAM	
PIERCE	DATE	06JUL20	SHU SMA
	BY	19MAY20	NDA SMA
VELOCITY	MODEL	31MAR20	NDA JBL
	NO.	35328AD-SH1	
DRAWN BY		SHU	23MAR20
CHECKED BY		SMA	27MAR20
SHEET SIZE		D	SHEET NO. 1 OF 2