



- HOSEBED CAPACITIES**
- ① 300' OF 2.50" D.J. POLY HOSE
 - ② 1500' OF 5.00" D.J. POLY HOSE
 - ③ 300' OF 1.75" D.J. POLY HOSE

ALUMINUM BODY MAXIMUM O.A.H. 120.00" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. BATTERY CHARGER LOCATED IN COMPARTMENT LS3
- 2. DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- 3. ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF LOCATED IN COMPARTMENTS LS1, RS1, RS3, B1
- 4. ONE ADJUSTABLE SLIDE-OUT TRAY IN COMPARTMENT LS1
- 5. ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENTS LS1, RS1 AND B1
- 6. ONE SWING-OUT ALUMINUM TOOL BOARD IN COMPARTMENT RS2
- 7. ONE SLIDE-OUT ALUMINUM TOOL BOARD IN COMPARTMENT LS3
- 8. FOAM PRO 1600 SINGLE AGENT FOAM SYSTEM LOCATED PER SHOP ORDER

REV	DATE	BY	CH	ARROW	XT
25NOV20	JWO	CHR	MAKE		
05NOV20	JWO	PJP	PIERCE		
24SEP20	JWO	CDU	MODEL		

		JOB NO.	35365
		SCALE	DATE
TITLE 1250-750 WATER/25 FOAM, 152" BODY, TOP MOUNT, DELUGE SPEEDLAYS, LADDER COMPT, FOAM SYSTEM, LIGHT TOWER	FOR LUFKIN FIRE DEPARTMENT LUFKIN, TEXAS	DRAWN BY	JWO
		CHECKED BY	WKL
DWG NO.	35365AD	SHEET SIZE	D
		SHEET NO.	1 OF 1