



- HOSEBED CAPACITIES**
- ① 200' OF 2.50" D.J. POLY HOSE
  - ② 400' OF 2.50" D.J. POLY HOSE
  - ③ WALKWAY
  - ④ 800' OF 4.00" D.J. POLY HOSE

ALUMINUM BODY    MAXIMUM O.A.H. 117.00"    MAXIMUM O.A.L. 366.00"    MAXIMUM O.A.W. 102.00"    SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. BATTERY CHARGER LOCATED IN COMPARTMENT-LS3
- 2. TWO ELECTRIC CERAMIC HEATERS IN THE CAB
- 3. ONE 120V DUPLEX RECEPTACLE LOCATED IN CAB
- 4. L.E.D. LIGHT STRIPS WALKING SURFACE LIGHTING LOCATED IN THE CARGO AREA

REV	DATE	BY	CH	ENFORCER
27JAN21	BST	JJR		
29DEC20	BST	JJR		
20NOV20	BST	JJR		
23SEP20	BST	JJR		

		JOB NO.	35492-01-05
		SCALE	1:24
TITLE	1750-D-500P W/40 GAL. FOAM CELL, DELUGE 161" PUMPER RESCUE BODY, LADDER TUNNEL THRU TANK	DRAWN BY	BST
FOR	WINNIPEG FIRE DEPARTMENT WINNIPEG, MB CANADA	CHECKED BY	JJR
DWG NO.	35492AD-SH1	SHEET SIZE	D
		SHEET NO.	1 OF 2