



ALUMINUM BODY MAXIMUM O.A.L. 400.75" MAXIMUM O.A.H. 113.50" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGE INDICATOR LOCATED NEAR D.S. SEAT RISER WITH BRACKET
- ONE HANNAY ELECTRIC REWIND CORD REEL ELFCR1622-14-16 LOCATED IN HATCH ABOVE P3 WITH 200' OF 10/3 CABLE AND CIRCLE-D JUNCTION BOX
- ONSPOT AUTOMATIC TIRE CHAINS
- DIF WHEEL CHOCKS AND MOUNTING BRACKETS

REV	DATE	BY	CH	ARROW-XT
24JUN21	JWO	ZWE		
27JAN21	JWO	KBO		
12NOV20	JWO	CDU		

		JOB NO.	35673	
		SCALE	1:24	
TITLE	1500-D-1000P, 970 GAL OF WATER W/30 GAL FOAM CELL 184" HDRP BODY, LADDERS THRU BODY, (2) CROSSLAYS		DATE	
FOR	OXFORD FIRE CENTER FIRE COMPANY OXFORD, CONNECTICUT		DRAWN BY	JWO
DWG NO.	35673AD-SH1		CHECKED BY	CDU
			SHEET SIZE	D
			SHEET NO.	1 OF 1