



BODY 110' Single Axle Platform Aluminum Body	WATER TANK 500 Gallon Poly Water Tank
COMPT, LEFT SIDE FRONT Full Height RollUp Forward	Foam System Plumbing For Future Foam System
COMPT, LEFT SIDE REAR Full Height RollUp Rearward	Foam Cell 20 Gallon Foam Cell, Non-Reducing Water
COMPT, RIGHT SIDE FRONT Full Height RollUp Forward	
COMPT, RIGHT SIDE REAR Full Height RollUp Rearward	

CHASSIS Enforcer Chassis 500 HP Cummins X12 Engine	CAB 7010 Notched Enforcer Cab 19" Extended Stainless Steel Bumper	AXLE, FRONT, CUSTOM 24,000 Lb TAK-4 Axle AXLE, REAR 33,500 Lb Meritor Axle	TRANSMISSION Allison 5th Gen, 4500 EV5 P	PUMPHOUSE 45" Control Zone Side Mount PUMP 2000 GPM Waterous CSU	CROSSLAYS, 1.50" (2) 1.50" Standard Capacity CROSSLAYS, 2.50" (1) 2.50" Standard Capacity	SPEEDLAYS Speedlays Not Required GENERATOR Generator Not Required	CUSTOMER APPROVAL APPROVED BY: _____ DATE: _____	Pierce MANUFACTURING INC.	JOB NO. 35868 SCALE 1:24 DATE _____ DRAWN BY LWE 04NOV20 CHECKED BY THS 5NOV20 SHEET SIZE D SHEET NO. 1 OF 1
NOTE DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.									
1. ONE 1.50" OUTLET WITH 2.00" PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY 2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB 3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL 4. BATTERY CHARGER LOCATED BEHIND DRIVERS SEAT 5. BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE CAB 6. SIX ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER 7. FOUR FLOOR MOUNTED SLIDE-OUT TRAYS IN COMPARTMENTS PER SHOP ORDER 8. NON-RAISED AERIAL PEDESTAL 9. 1250 GPM HIGH FLOW WATERWAY 10. RUNG LIGHTING ON AERIAL LADDER 11. 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNABLE 12. NO LIMITED RESTRICTION 13. MOUNTING PROVISIONS FOR FRONT INLET									
REV	DATE	BY	CH	ENFORCER	CHASSIS DATA	MAKE	PIERCE	MODEL	TITLE
									110' ASCENDANT AERIAL LADDER AND BODY ASSEMBLY
									PIERCE FIELD UNIT APPLETON, WI
									DWG NO. 35868AD