



ALUMINUM BODY      MAXIMUM O.A.H. 122.00"

OVERALL HEIGHT - 122.00"	OVERALL WIDTH - 117.75"	BODY MATERIAL - ALUMINUM
MAX OAL - 372.00"	WHEELBASE - 180.50"	CAB TO AXLE - 110.50"
		JOB NO. 36298
		SCALE 1:24      DATE
TITLE 1500-D-750 GAL POLY W/30 GAL FOAM CELL, 177" RESCUE (3)XLAYS, DELUGE, BOOSTER REELS, LADDERS THRU BODY	FOR COUNTY OF MAUI FIRE DEPARTMENT MAUI, HAWAII	DRAWN BY JWO      DATE 01MAR21
REV 12JUL21      JWO      AZA	28MAY21      JWO      AZA	CHECKED BY AZA      DATE 01MAR21
11MAR21      JWO      AZA	REV      DATE      BY      CH	SHEET SIZE D      SHEET NO. 1 OF 2
DWG NO. 36298AD-SH1		

- NOTE**  
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.
- 5/STL SCUFFPLATE ON EACH CAB DOOR JAMB
  - BATTERY CHARGER LOCATED BEHIND DRIVERS ON CAB EMS COMPARTMENT
  - BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SEAT RISER
  - PULL STRAPS W/FOOTMAN LOOPS FOR SIDE COMPARTMENT DOORS INCLUDING CROSSSLAY DOORS
  - 12V L.E.D. LIGHT STRIPS LOCATED IN HOSEBED
  - 5/STL SCUFFPLATE ON FRONT BULKHEADS
  - 5/STL SCUFFPLATE AROUND DEF AND FUEL FILL OPENINGS
  - 5/STL SCUFFPLATE ON FRONT CORNERS OF BODY
  - 5/STL SCUFFPLATE AROUND AIR BOTTLE COMPARTMENT OPENINGS
  - 5/STL SCUFFPLATE ON THE FRONT FACE OF THE CROSSSLAY AREA
  - 5/STL SCUFFPLATE ON VERTICAL SURFACES OF REAR STEP AREA OF HATCH
  - TWO HANNAY BOOSTER REELS MODEL SBEF30-23-24 LOCATED IN CARGO AREA EACH WITH 150' OF 1.00" BOOSTER HOSE
  - WHELEN HOWLER AUXILIARY SIREN (SPEAKER SYSTEM BEHIND RIGHT SIDE OF FRONT BUMPER)
  - 5/STL SCUFFPLATES REAR CAB CORNERS
  - 5/STL SCUFFPLATES REAR BODY CORNERS
  - ALUMINUM TREADPLATE INSTALLED ON THE FLOOR OF COMPARTMENT RS3