


Temporary outdoor security

Heras Mobile Fencing & Security

Heras Mobile is the reliable specialist for the production, sale and rental of solutions for temporary security. It was Heras who invented the construction fence in 1966. Founded in 1952, Heras Mobile is currently operational in 24 countries.

Heras Mobile is a stable entity. We understand the problems of lessors and end-users.



All Heras Mobile construction fence installations have a CE certificate and therefore comply with safety regulations laid down within the European Economic Area. We gave our products important added values, such as excellent logistics and detailed assembly instructions. High-quality accessories provide additional security for your workers, end-users and the environment.

Europe's largest in temporary security

Heras Mobile is European market leader in temporary security solutions. This we achieved by keeping in touch with the market. The possibilities are unlimited, our staff is competent and flexible and production is ecologically responsible.

Reliable solutions

Heras Mobile offers reliable solutions for protecting temporary limits. Our ambition is an optimal price/quality balance. Being customer-oriented is in our blood. You and your customers will get a good and safe feeling with our way of working and the solutions we offer.



Heras Mobile values Safety, Health and Environment

We contribute to sustainability within the temporary fencing industry

Heras Mobile Fencing & Security's three European production units are designed to produce as efficiently as possible. Energy and CO2 reduction are achieved by applying innovative techniques and clever planning. Our aim is to continuously invest in future-proof, more energy-efficient plants.

Market leader Heras Mobile invests in sustainable and secure production, process innovation and enterprising. We do this by implementing our ESG policy and safety in our day-to-day tasks, but also by looking at better solutions with partners and suppliers.

Safety, Health and Environment

Heras Mobile endorses strict policies on Safety, Health and Environment. Together with our staff, suppliers and customers we sustain the chain. Our standard policies are:

Safety

Zero accidents and fatalities in production, transport and assembly. Safety is our priority and therefore we have a certified system for security management.


Health

A safe environment, a good working atmosphere and good working conditions play a key role. Together we avoid incidents and reduce sick leave. We also encourage the personal development of our employees.

Environment

We want to reduce our impact on the environment. To achieve this, we focus on our own activities and our impact in the value chain. Together with our partners, we are working to reduce emissions and achieve a circular economy.






Mobile fence M550 (8 x 11.5ft)

Specifications

Article Code C1200000 Dimensions (ft) 8' x 11.5' 1.18" x 1.65" Tube diameter (in) Tube-H thickness (in) 0.059" Tube-V thickness (in) 0.059" Extra Tube diameter (in) 1.18" Extra Tube thickness (in) 0.059" Wire thickness (in) 0.157" x 0.118"

Mesh opening (in) 5.91" x 1.50"

Package quantity Weight (lbs) 90




Mobile Fence M500 + Corner Brackets

Specifications

Article code C0102000 Dimensions (in) 6.6' x 11.5' Tube diameter (in) 1.18" x 1.65" Tube-H thickness (in) 0.049" Tube-V thickness (in) 0.049"

Wire thickness (in) 0.157" x 0.118" Mesh opening (in) 6.3" x 1.57" Package quantity 80 (68+12) Weight (lbs) 53




Mobile fence M450 + Corner Brackets + 3xV

Specifications

Article code C2104000 Dimensions (ft) 6.6' x 11.5' Tube diameter (in) 1.18" x 1.65" Tube-H thickness (in) 0.049" Tube-V thickness (in) 0.049" Extra Tube diameter (in) 1.18" Extra Tube thickness (in) 0.049"

Wire thickness (in) 0.118" x 0.098" Mesh opening (in) 13.78" x 1.57" Package quantity 80 (68+12) Weight (lbs) 43




Mobile Fence M450 + Corner Brackets

Specifications

Article code C2102000 Dimensions (ft) 6.6' x 11.5' Tube diameter (in) 1.18" x 1.65" Tube-H thickness (in) 0.049" Tube-V thickness (in) 0.049"

Wire thickness (in) 0.118" x 0.098" Mesh opening (in) 13.78" x 1.57" Package quantity 80 (68+12) Weight (lbs) 40



Mobile Fence M400 + Corner Brackets

Specifications

 Article code
 C0221000

 Dimensions (ft)
 6.6' x 11.5'


 Tube diameter (in)
 1.18" x 1.65"

 Tube-H thickness (in)
 0.049"

 Tube-V thickness (in)
 0.049"

Wire thickness (in) $0.157" \times 0.118"$ Mesh opening (in) $9.84" \times 3.94"$ Package quantity80 (68+12)

Weight (lbs) 37



Mobile Fence M400 + Tube-H

Specifications

Article code C0209000

Dimensions (ft) 6.6' x 11.5'

Tube diameter (in) 1.18" x 1.65"

Tube-H thickness (in) 0.049"

Tube-V thickness (in) 0.049"

Extra Tube diameter (in) 1.18"

Extra Tube thickness (in) 0.049"


 Wire thickness (in)
 0.157" x 0.118"

 Mesh opening (in)
 9.84" x 3.94"

 Package quantity
 80 (68+12)

 Weight (lbs)
 44

weight (ibs) 44



Mobile Fence M400

Specifications

 Article code
 C0207000

 Dimensions (ft)
 6.6' x 11.5'

 Tube diameter (in)
 1.18" x 1.65"

 Tube-H thickness (in)
 0.049"

 Tube-V thickness (in)
 0.049"

 Wire thickness (in)
 $0.157" \times 0.118"$

 Mesh opening (in)
 $9.84" \times 3.94"$

 Package quantity
 80 (68+12)

Weight (lbs) 3



Fitting Panel M400 (6.6 x 7.4ft)

Specifications

 Article code
 C0226000

 Dimensions (ft)
 6.6' x 7.4'

 Tube diameter (in)
 1.18" x 1.65"


 Tube-H thickness (in)
 0.049"

 Tube-V thickness (in)
 0.049"

 Wire thickness (in)
 $0.157" \times 0.118"$

 Mesh opening (in)
 $9.84" \times 3.94"$

Package quantity 68 Weight (lbs) 27.5



Mobile Fence M300

Specifications


 Article code
 C5107000

 Dimensions (ft)
 6.6' x 11.5'

 Tube diameter (in)
 1.18" x 1.50"

 Tube-H thickness (in)
 0.049"

 Tube-V thickness (in)
 0.039"



Mobile Fence M300 + Corner Brackets

Specifications


 $\begin{array}{lll} \textbf{Article code} & \textbf{C5121000} \\ \textbf{Dimensions (ft)} & \textbf{6.6'} \times \textbf{11.5'} \\ \textbf{Tube diameter (in)} & \textbf{1.18''} \times \textbf{1.50''} \\ \textbf{Tube-H thickness (in)} & \textbf{0.049''} \\ \textbf{Tube-V thickness (in)} & \textbf{0.039''} \\ \end{array}$

 Wire thickness (in)
 0.118" x 0.098"

 Mesh opening (in)
 9.84" x 3.94"

 Package quantity
 86 (72+14)

 Weight (lbs)
 29



Mobile Fence M350

Specifications

 Article code
 C0300000

 Dimensions (ft)
 6.6' x 11.5'

 Tube diameter (in)
 0.87" x 1.50"


 Tube-H thickness (in)
 0.039"

 Tube-V thickness (in)
 0.039"

Wire thickness (in) $0.118" \times 0.098"$ Mesh opening (in) $13.98" \times 3.94"$ Package quantity105 (84+21)

Weight (lbs) 22





Mobile Fence Round Top Anti-Climb Tube-V

Specifications

Article Code C4710000 Dimensions (ft) 6.4' x 11.5' Tube diameter (in) 1.50" x 1.50" 0.039" Tube-H thickness (in) Tube-V thickness (in) 0.039" Extra Tube diameter (in) 1.18" Extra Tube thickness (in) 0.049"


Wire thickness (in) 0.118" x 0.098" 13.78" x 1.57" Mesh opening (in) Package quantity 70 (60+10) Weight (lbs) 40



Specifications

Article Code C4700000 Dimensions (ft) 6.4' x 11.5' Tube diameter (in) 1.50" x 1.50" 0.039" Tube-H thickness (in) Tube-V thickness (in) 0.039"

Wire thickness (in) 0.118" x 0.098" Mesh opening (in) 13.78" x 1.57" Package quantity 70 (60+10) 36.5 Weight (lbs)




Mobile Fence Round Top

Specifications


Article code C4600000 Dimensions (ft) 6.4' x 11.5' Tube diameter (in) 1.50" x 1.50" Tube-H thickness (in) 0.039" Tube-V thickness (in) 0.039"

Wire thickness (in) 0.118" x 0.098" 9.84" x 3.94" Mesh opening (in) Package quantity 70 (60+10)

Weight (lbs)







Pedestrian Gate Round Top

Specifications

Article code P1502
Dimensions (ft) 6.6' x 3.8'
Package quantity 1
Weight (lbs) 32



Vehicle Gate Round Top

Specifications

Accessoires



42/60 High Security coupler + Hinge ring

Mobile Fence M100 (3.9 x 11.5ft) + Hook & Eye



Specifications

 Article code
 C1303000

 Dimensions (ft)
 3.9' x 11.5'

 Tube diameter (in)
 1.18" x 1.65"

 Tube-H thickness (in)
 0.049"

 Tube-V thickness (in)
 0.049"

 Wire thickness (in)
 $0.118'' \times 0.118''$

 Mesh opening (in)
 $9.84'' \times 3.94''$

Package quantity 68 Weight (lbs) 25

Crush Barrier M135 - 16 bars



Specifications

Article code C3600001 Dimensions (ft) 3.6' X 7.5' Bar distance (in) 4.45" **Vertical Bar number** 1.50" Frame Tube diameter (in) Frame Tube thickness (in) 0.039" Vertical Bar diameter (in) 0.47" Vertical Bar thickness (in) 0.039" Package quantity 25 24 Weight (lbs)

Crush Barrier M125 - 19 bars



Specifications

Article code C1400000 Dimensions (ft) 3.6' X 8.2' 3.94" Bar distance (in) **Vertical Bar number** 19 Frame Tube diameter (in) 1.50" Frame Tube thickness (in) 0.059" Vertical Bar diameter (in) 0.59" 0.079" Vertical Bar thickness (in) Package quantity 55 Weight (lbs) 35





Noise Control Barrier 2.0

Specifications

Article code: E0807
Dimensions (ft) 6.6' x 4'
Package quantity 1
Weight (lbs) 17.5



Cityfence M800 (RAL 9010)

Specifications

Article code C1700000

Dimensions (ft) 6.6' x 7.1'

Profile dimensions (ft) 1.65"

Tube-V thickness (in) 0.049"

Package quantity 28

Weight (lbs) 57



Combifence M825 (RAL 5010)

Specifications

 $\begin{array}{lll} \textbf{Article code} & C2600000 \\ \textbf{Dimensions (ft)} & 6.6' \times 7.1' \\ \textbf{Profile dimensions (ft)} & 3.6' \times 6.8' \\ \textbf{Tube diameter (in)} & 1.18'' \times 1.65'' \\ \textbf{Tube-H thickness (in)} & 0.049'' \\ \textbf{Tube-V thickness (in)} & 0.049'' \\ \end{array}$

Package quantity 28 Weight (lbs) 55





Sliding fence construction set

Specifications

Article code P0800

Dimensions (ft) 6.6' x 11.8'

Clear width (ft) 11'

Required installation space (ft) 23'

Dimensions depth (in) 6"

Weight (lbs) 33




Pedestrian Gate M90 (3.9ft)

Specifications

Mesh opening (in) 11.81" × 2.95"

Package quantity 25 Weight (lbs) 29



Pedestrian Gate M500 (3.9ft)

Specifications

Article codeP0500Dimensions (ft) $6.6' \times 3.9'$ Clear width (ft)3.6'Mesh opening (in) $6.30'' \times 1.57''$ Package quantity25

Weight (lbs) 32

Accessoires











Accessoires

Safety





coupler







Stability



Recycled footing 55 lbs



Recycled footing with gap 39.7 lbs



Recycled footing 30 lbs



Concrete footing 77 lbs




52 lbs




brace









Temporary access and blinding







Tarpaulin black (also available in blue & white)



fire-retardant 164 ft





Storage and transport



Transport rack PVC for 28 fences vertical



Transport rack for crush barriers



Transport rack-V for 30 fences + foot + coupler



Transport rack for 25 fences vertical



Transport rack-V for 30 fences



Added values for you

Over Heras Mobile Fencing & Security

Heras Mobile Fencing & Security is a company specialised in securing temporary locations. Heras Mobile is a stable European partner. We want to remain the most reliable supplier and expert in temporary outdoor security. On the basis of our professional, friendly and problem-solving mentality.

Heras Mobile is the specialist in temporary security. You will find our 'A'-ranked qualities on three of the six continents. Europe is our solid home market. In the Benelux we have our own rental section with a true know-how of outdoor security. Large projects can easily be scheduled with a 100% stable company with various production units. We are glad to help you on a basis of service, mutual respect and trust. Reliability for us means respecting agreements.

Heras Mobile in short

As European market leader, Heras Mobile has more than 70 years' experience in temporary security and is the inventor of the security fence. Our friendly, involved and reliable workers also know that a better service can make all the difference. Heras Mobile' production is state-of-the-art in Belgium, France and the Czech Republic. We have a wide range on offer, from simple and functional security fences to the safest and strongest protection of temporary locations.

Heras Mobile Fencing & Security
PO Box 145, 5680 AC
Best
THE NETHERLANDS
T+31 (0)499 551 508

Disclaimer. There are no rights to be derived from the technical specification. You should always consider up to 10% tolerance deviations. Heras herewith complies with NEN-EN 10305-3 © Heras. Versie 1.0 2023 | EXPORT US

