Osmose_®

Guy Markers

LONG LASTING, HIGHLY VISIBLE PROTECTION

Osmose brand Guy Markers offer long-lasting, highly visible protection for your guy wires. The addition of special additives helps retard UV light degradation. Material quality and generous wall thickness help Osmose Guy Markers resist both cracking and shattering.

- ✓ Medium-density polyethylene, specifically formulated for outdoor use
- ✓ Bright yellow stands out and resists fading
- ✓ Generous wall thickness of .080" helps prevent cracking and shattering
- ✓ Available in three diameters: 1-1/8", 1-3/8", 2-1/2"
- ✓ Sold in 8-foot sections

Specifications

Property	Method ASTM	Value
Tensile Yield 2'/min.	D 1248	4,000 psi
Elongation at break 2' min.	D 1248	950%
Tensile Impact	D 1822	120 ft.lb/in ²
Flexural Stiffness	D 747	100,000 psi
Environmental Stress Crack Resistance	D 1692	175 hrs./5
F. Softening Point (Vicat)	D 1525	254 F. Temp.
Brittleness Point	D 746	-94 F.
Wall Thickness		.080″

Ordering Information

Catalog Number	Size	Wall Thickness	# / Pallet	Shipping Weight
70-060-005-188	1-1/8" x 8'	.080″	250	400 lbs/pallet
70-060-005-388	1-3/8" x 8'	.080"	250	500 lbs/pallet
70-060-005-258	2-1/2" x 8'	.080″	125	375 lbs/pallet

For more information or to place an order: 770.632.6700 opt. 3 or products@osmose.com