



LAPAROSCOPIC SURGERY

AESCULAP® Caiman®

ADVANCED BIPOLAR SEAL AND CUT TECHNOLOGY

AESCULAP® Caiman® ADVANCED BIPOLAR SEAL AND CUT TECHNOLOGY

Caiman® is intended to be used as a multipurpose vessel sealing instrument in laparoscopic and open surgery within the surgical fields of general surgery, gynecology, urology and thoracic surgery.

ONE SEAL CONFIDENCE

State of the art vessel sealing with only one energy activation

UNIFORM TISSUE COMPRESSION

Leads to consistent sealing quality from distal to proximal tip

TIP FIRST CLOSURE

Retains tissues within the jaws for improved compression

TISSUE DISSECTION


Fine curved Maryland jaw design allows increased dissection performance and enhanced tip visualization


LONG JAW TIP

Enlarged vessel sealing length and improved surgical efficiency

80 DEGREE ARTICULATION JAW

Allows simplified navigation in challenging anatomy






Caiman® INSTRUMENTS

seal vessels up to 7 mm in diameter and feature an average thermal spread of less than 1 mm.* Effectively seals with virtually no adhesion or charring.

80° ARTICULATING JAW

The Caiman® line are the first RF tissue and vessel sealing instruments with an articulating jaw – providing a more flexible, agile device for surgical procedures.

*Data on file at Aesculap AG.



STRONG UNIFORM COMPRESSION

within the jaw is key to creating a confident seal. Compression force in other devices may decline from proximal to distal end influencing the sealing quality.*

Red represents minimum required pressure (or greater). Blue represents insufficient pressure. Minimum required pressures based on Aesculap calculated requirements. Graphs of minimum required pressure produced on a synthetic tissue model.


^{*}Data on file at Aesculap AG.

ORDERING INFORMATION

		Shaft diameter	Working length	Pcs per pack
Caiman®!	5, NON ARTICULATING JAW	V		
PL718SU*	/ PL738SU**	5 mm	24 cm	6
	/ PL740SU**	5 mm	36 cm	6
	/ PL742SU**	5 mm	44 cm	6
Caiman® (5, NON ARTICULATING MA	RYLAND JAW		
PL754SU*	/ PL774SU**	5 mm	12.5 cm	6
PL755SU*	/ PL775SU**	5 mm	17 cm	6
PL750SU*	/ PL770SU**	5 mm	36 cm	6
PL752SU*	/ PL772SU**	5 mm	44 cm	6
Caiman® !	5, ARTICULATING JAW			
PL719SU*	/ PL739SU**	5 mm	24 cm	6
PL721SU*	/ PL741SU**	5 mm	36 cm	6
PL723SU*	/ PL743SU**	5 mm	44 cm	6
Caiman®	5, ARTICULATING MARYLAI	ND JAW		
PI 751SU*	PL751SU* / PL771SU**		36 cm	6
	/ PL773SU**	5 mm 5 mm	44 cm	6
Caiman®	12, ARTICULATING JAW			
Caiman® 1	12, ARTICULATING JAW	12 mm	24 cm	3
	12, ARTICULATING JAW	12 mm 12 mm	24 cm 44 cm	3 3
PL730SU PL731SU LEKTRAFL	12, ARTICULATING JAW JSE RF-GENERATOR (WITH	12 mm		
PL730SU PL731SU LEKTRAFU GN200		12 mm OUT MAIN CABLE)		
PL730SU PL731SU LEKTRAFU GN200	JSE RF-GENERATOR (WITH JSE RF-GENERATOR ACCES	12 mm OUT MAIN CABLE)	44 cm	
PL730SU PL731SU LEKTRAFU GN200 LEKTRAFU	USE RF-GENERATOR (WITH USE RF-GENERATOR ACCES E730 Main Cable, 0	OUT MAIN CABLE)	44 cm plug, 1.5 m / 5 m	
PL730SU PL731SU LEKTRAFU GN200 LEKTRAFU TE780 / TE	USE RF-GENERATOR (WITH USE RF-GENERATOR ACCES E730 Main Cable, 0 Main Cable f	12 mm OUT MAIN CABLE) SORIES Grounding-type European or Great Britain and Irelan	44 cm plug, 1.5 m / 5 m d, 5 m	
PL730SU PL731SU LEKTRAFL GN200 LEKTRAFL TE780 / TE TE734	USE RF-GENERATOR (WITH USE RF-GENERATOR ACCES E730 Main Cable, 0 Main Cable f Main Cable f	12 mm OUT MAIN CABLE) SORIES Grounding-type European	44 cm plug, 1.5 m / 5 m d, 5 m , 3.5 m	3
PL730SU PL731SU LEKTRAFU GN200 LEKTRAFU TE780 / TE TE734 TE735	USE RF-GENERATOR (WITH USE RF-GENERATOR ACCES E730 Main Cable, 0 Main Cable f Main Cable f E736 Main Cable, 0 Unit cart wit	DUT MAIN CABLE) SORIES Grounding-type European or Great Britain and Irelan or USA, Canada and Japan IEC 60320 connector (non-th sliding handle for electrons)	plug, 1.5 m / 5 m d, 5 m , 3.5 m -heating equipmen	3
PL730SU PL731SU LEKTRAFL GN200 LEKTRAFL TE780 / TE TE734 TE735 TE676 / TE	USE RF-GENERATOR (WITH USE RF-GENERATOR ACCES E730 Main Cable, 0 Main Cable f Main Cable f E736 Main Cable, 0 Unit cart wit	DUT MAIN CABLE) SORIES Grounding-type European or Great Britain and Irelan for USA, Canada and Japan IEC 60320 connector (non-	plug, 1.5 m / 5 m d, 5 m , 3.5 m -heating equipmen	3
PL730SU PL731SU LEKTRAFL GN200 LEKTRAFL TE780 / TE TE734 TE735 TE676 / TE	USE RF-GENERATOR (WITH USE RF-GENERATOR ACCES E730 Main Cable, 0 Main Cable f Main Cable f E736 Main Cable, 0 Unit cart wit	DUT MAIN CABLE) SORIES Grounding-type European or Great Britain and Irelan or USA, Canada and Japan IEC 60320 connector (non-th sliding handle for electrons)	plug, 1.5 m / 5 m d, 5 m , 3.5 m -heating equipmen	3
PL730SU PL731SU LEKTRAFL GN200 LEKTRAFL TE780 / TE TE734 TE735 TE676 / TI GN330	USE RF-GENERATOR (WITHOUSE RF-GENERATOR ACCES Main Cable, Main Cable for Main Cable, Main	DUT MAIN CABLE) SORIES Grounding-type European or Great Britain and Irelan or USA, Canada and Japan IEC 60320 connector (non-th sliding handle for electrons)	plug, 1.5 m / 5 m d, 5 m , 3.5 m -heating equipmen	3

 $^{^{\}ast}$ $\,$ Ordering number for the following countries: CN, KR, BR, JP, RU, BO, CO, MY, SG, AR, EC, TW

^{**} Ordering number for the following countries: UK, DE, FR, ES, PL, IT, SE, CZ, NL, BE, LU, PT, AT, CH, BA, DK, FI, IE, SK, NO, TR, HU, RO, BG, CY, SI, GR, KZ, US, ID, PH, AU, NZ, HK, MX, PE, AZ, CL, JO, KW, LY, NC, IN, VN



Caiman® Seal and Cut instruments feature patented mechanisms which are key to enable high uniform tissue compression and avoid tissue slippage. Excellent vessel sealing quality and simplified tissue positioning in the jaw can be achieved.

LONG JAW TIP

Enlarged vessel sealing length and improved surgical efficiency.

AESCULAP® - a B. Braun brand

Aesculap AG \mid Am Aesculap-Platz \mid 78532 Tuttlingen \mid Germany Phone +49 7461 95-0 \mid Fax +49 7461 95-26 00 \mid www.aesculap.com