

YOUR WORKING AT HEIGHT PARTNER

Low-level fibreglass platforms

The HLS GRP Podium brings you all the advantages of a fibreglass access solution, non conductive up to 100 kilovolt per foot, in the shape of a compact tower.

Conforming to BS 8620

Non-conductive (100kv/ft)

Chemical resistant

Weather resistant

Spark resistant

Visible colour

Non-slip platform deck

Non-slip step treads

Anti-slip feet

Captive ladder

Locking gate

In-line castors

BS 8620.



YOUR WORKING AT HEIGHT PARTNER

The podiums visible colour makes it stand out in a busy work environment, whilst a captive ladder, locking gate and in-line castors give it integral benefits. Working at height is made safer with the non-slip platform deck, step treads, and anti-slip feet. The podium is also chemical, weather and spark resistant.

Platform height	950mm	1250mm	1500mm
Working height	2950mm	3250mm	3500mm
Overall height	2000mm	2300mm	2550mm
Working platform	607 x 625mm	607 x 625mm	607 x 625mm
Deployed footprint	1405 x 745mm	1600 x 1150mm	1700 x 1150mm
Stowed dimensions	2000 x 745 x 365mm	2250 x 745 x 485mm	2550 x 745 x 485mm
Safe working load	150kg	150kg	150kg
Weight	44kg	50kg	52kg

