

YOUR WORKING AT HEIGHT PARTNER

Specification:

- 360 working platform – 550mm x 400mm
- Glass fibre frame with Aluminium treads
- Aluminium handrails as standard
- Enclosed platform on three sides for safety
- Folds flat for storage and transportation
- Insulated and non-conductive whilst in use
- Ergonomically designed for industrial work
- HSE Work at Height Regulations 2005 compliant to work two-handed for short duration jobs
- BS EN131 Kitemarked and complies to: ANSI 14-5 and ESI 13-1

Optional Extras:

- Security webbing strap (shown)
- Yellow plastic coated handrail (shown)
- Detachable handrails
- Glass fibre platform and treads (non-spark)
- Wheels at rear
- Level-Eze Stability System
- Detachable tool tray or top cross rail as a tray
- Laddertag for inspection and maintenance
- Marking with company details for security
- Metal grid feet

Also available in aluminium



Tool Tray

HLS EXTRA WIDE PLATFORM STEPS PRICE LIST					Optional Extras / Accessories	
ALUMINIUM TREADS					Accessory	
Code	Overall Length	Platform Height	Number of Treads	Approx. Weight		
HLS 02	1.55m	0.46m	2	11.5kg	Detachable tool tray	
HLS 03	1.80m	0.71m	3	13.5kg	Handrail Bungs (set of 4)	
HLS 04	2.05m	0.96m	4	14.0kg	Plastic coated handrails	
HLS 05	2.31m	1.19m	5	16.0kg	Travel wheels at rear	
HLS 06	2.56m	1.44m	6	19.0kg	Ladder Tag	
HLS 07	2.82m	1.64m	7	20.0kg	Security webbing strap gate	
HLS 08	3.07m	1.89m	8	22.0kg	Bar Gate	
HLS 09	3.32m	2.19m	9	23.0kg	Swing Gate	
HLS 10	3.57m	2.44m	10	24.0kg	Large feet for open mesh grids	
HLS 11	3.82m	2.69m	11	26.0kg	Self-levelling feet system	
GLASS FIBRE TREADS						
Code	Overall Length	Platform Height	Number of Treads	Approx. Weight		
HLS GF02	1.55m	0.46m	2	11.5kg		
HLS GF03	1.80m	0.71m	3	13.5kg		
HLS GF04	2.05m	0.96m	4	14.0kg		
HLS GF05	2.31m	1.19m	5	16.0kg		
HLS GF06	2.56m	1.44m	6	19.0kg		
HLS GF07	2.82m	1.64m	7	20.0kg		
HLS GF08	3.07m	1.89m	8	22.0kg		
HLS GF09	3.32m	2.19m	9	23.0kg		
HLS GF10	3.57m	2.44m	10	24.0kg		
HLS GF11	3.82m	2.69m	11	26.0kg		



0113 287 8446

