

YOUR WORKING AT HEIGHT PARTNER

LIGHTWEIGHT NON-POWERED ACCESS PLATFORM

PATENT PENDING

- Working height 4 meters
- Safe working load max. 150 kg
- Total weight 228-239 kg
- Max. wind 12.5 m/s
- Compact size
- Automatic, anti-surfing system
- Lockable swivel castors
- Advanced gas spring powered hoisting mechanism
- Eco friendly, hydraulic oil free
- Indoor & outdoor rated
- Optional stabilisers for outdoor usage
- Compliant with Machinery Directive 2006/42/EC and EN 280/2013 & EN 1004/2004 standards
- CE certified

IXOLIFT 400WS



TECHNICAL SPECIFICATIONS	IXOLIFT 400W	IXOLIFT 400WS
WORKING HEIGHT	3974 mm	
MAX. WORKING LOAD	150 kg	
MAX. PLATFORM HEIGHT	1974 mm	
MIN. PLATFORM HEIGHT	974 mm	
PLATFORM SIZE	526 mm x 556 mm	
STOWED HEIGHT	1970 mm	
STOWED LENGTH	1198 mm	
STOWED WIDTH	728 mm	
MAX. LENGTH WITH STABILISERS OUT	N/A	1500 mm
MAX. WIDTH WITH STABILISERS OUT	N/A	1668 mm
CLASSIFICATION	INDOOR RATED	INDOOR & OUTDOOR RATED
TOTAL WEIGHT	228 kg	239 kg



YOUR WORKING AT HEIGHT PARTNER



ADVANCED GAS SPRING
POWERED HOISTING
MECHANISM



AUTOMATIC ANTI-SURFING
BRAKES



AUTOMATIC FINGER
PROTECTION SYSTEM
(OPTIONAL)



SAFETY HARNESS
CONNECTOR POINTS
EN 280/2013 3kN FORCE



STABILISERS ENABLING
OUTDOOR RATING
EN 280/2013 12.5 M/S WIND



TOOL BOXES
(OPTIONAL)



SAFE STEPS
EN 1004/2004



ROBUST CONSTRUCTION



HEAVY DUTY, LOCKABLE
SWIVEL CASTOR WHEELS
WITH CORNER PROTECTOR
WHEELS

