



# SERIES 601, 604 & 605 CRYOGENIC FLEXIBLE HOSES

## 316 STAINLESS STEEL FLEXIBLE HOSES SERIES 601, 604, AND 605

Series 601 hoses are constructed of 1/4" I.D. teflon® lined stainless steel braid, rated for 3000 psig. The 601 hoses are fitted with 1/4" NPT brass end connections; they make excellent economical manifold pigtails.

The Series 604 & 605 hoses are constructed of double braided stainless steel, fitted with stainless steel 1/4" NPT end connections, rated for 3000 psig, and cleaned for oxygen service.

### Materials and Specifications

<b>Body:</b>	316L stainless steel
<b>Internals:</b>	stainless steel
<b>Flame barrier:</b>	stainless steel
<b>Elastomers:</b>	Neoprene

### Special Hoses

We can provide any of the hoses on this page in different lengths and with a wide variety of end fittings.



### 601 Series

- 1/4" I.D. Teflon® lined 316 stainless steel braided hose
- Rated for 3000 psig
- 601 1/4" NPT female x 1/4" NPT female
- 601MF 1/4" NPT male x 1/4" NPT female
- Cleaned for oxygen service.

### 604 & 605 Series

- 1/4" I.D. 316 stainless steel fitting and inner core with 304SS or 321SS double braided hose.  
Note: 605 Series has protective outer armor to provide greater safety and kink resistance
- Rated for 3000 psig
- 1/4" NPT female or male stainless steel end connections.
- Cleaned for oxygen service.

### Order Information

Part Number	Length	Part Number	Length	Part Number	Length
601-2	2 feet	604MF-2	2 feet	605M-2	2 feet
601MF-2	2 feet	604-3	3 feet	605MF-2	2 feet
601-3	3 feet	604M-3	3 feet	605-3	3 feet
601MF-3	3 feet	604MF-3	3 feet	605M-3	3 feet
601-6	6 feet	604-6	6 feet	605MF-3	3 feet
601MF-6	6 feet	604M-6	6 feet	605-6	6 feet
604-2	2 feet	604MF-6	6 feet	605M-6	6 feet
604M-2	2 feet	605-2	2 feet	605MF-6	6 feet