



# IN-LINE FILTER SERIES 7500

## FEATURES

- Compact in-line design with large filtration area.
- Sintered 316 stainless steel element.
- Choice of 1, 2, 5, 10, 50, or 100 micron filter element.

## SPECIFICATIONS

|                           |  |
|---------------------------|--|
| <b>OPERATING PRESSURE</b> | Brass: 3000 psig<br>316 SS: 6000 psig* |
|---------------------------|--|

## MATERIALS OF CONSTRUCTION

| MODEL | BODY   | SEALS  | FILTER ELEMENT      |
|-------|--------|--------|---------------------|
| 7510  | Brass  | Buna-N | 316 Stainless Steel |
| 7520  | 316 SS | Viton  | 316 Stainless Steel |



**SGD 7510-P4MM  
PICTURED**

## ORDER INFORMATION

| PART NUMBER       | DESCRIPTION                         |
|-------------------|-------------------------------------|
| SGD 7510-X-P4MM   | 1/4" NPT male x 1/4" NPT male       |
| SGD 7510-X-P4FF   | 1/4" NPT female x 1/4" NPT female   |
| SGD 7510-X-T4FF   | 1/4" compression x 1/4" compression |
| SGD 7510-X-P8MM   | 1/2" NPT male x 1/2" NPT male       |
| SGD 7510-X-P8FF   | 1/2" NPT female x 1/2" NPT female   |
| SGD 7520-X-P4MM   | 1/4" NPT male x 1/4" NPT male       |
| SGD 7520-X-P4FF   | 1/4" NPT female x 1/4" NPT female   |
| SGD 7520-X-T4FF   | 1/4" compression x 1/4" compression |
| SGD 7520-X-P8MM** | 1/2" NPT male x 1/2" NPT male       |
| SGD 7520-X-P8FF   | 1/2" NPT female x 1/2" NPT female   |

Other end fitting configurations are available.

X - Specify filter element 1, 2, 5, 10, 50 or 100 microns.

\* 2 micron filter operating pressure is 3000 psig.

\*\* 2 micron filter not available in 1/2" units.

*Can't find what you need? We will be happy to assist you to find the right filter to fit your needs.*