

## Hydraulic Rope Cutter



- EASY TO OPERATE
- ROBUST DESIGN
- REQUIRE A MINIMUM OF MAINTENANCE
- MADE IN NORWAY



## SPECIFICATION

Dimensions in cm	LWH 88 x 9 x 18
Frame	Aluminum
Max rope diameter	Ø 80mm
Weight in air	7 kg
Weight in water	5 kg
Max depth rating	4000m
Working pressure	140BAR – Ø40mm rope 210BAR – Ø80mm rope
Mechanical interface	Square profile 50x50 (use 2 x M8-bolts)
<sup>1</sup> Hydraulic interface	2 x 1/4" BSP Female

<sup>1</sup> If your ROV system isn't equipped with 2 spare valves on the valve pack - You will need HPU (if not present) and hydraulic valve pack in addition to make this cutter work – For more info, please contact us.

Sperre AS reserves the right to change prices and specifications without notice.  
 Sperre AS take reservations for errors and omissions in this data sheet.

DAT-066

Sperre AS – Telemark Teknologipark - Merdeveien 1 – 3676 Notodden, NORWAY

Email: [post@sperre-as.com](mailto:post@sperre-as.com)

Phone: +47 35 02 50 00

Web: <http://www.sperre-as.com>

