



PAR-P4DRIR-AI

4 Megapixel IP Plug & Play, Outdoor Dome, True AI, 65' IR Range, WDR, Audio Input, Built-in Mic, PoE/12VDC, Facial Rec

Features

- 4 Megapixel Resolution
- Fixed Lens
- Facial Recognition Capable with Compatible NVR
- True Day/Night with IR Range up to 65'
- True AI Human and Vehicle Classification for Line Crossing and Intrusion Detection
- Smart H.265/H.265+/H.265/Smart H.264/H.264+/H.264/MJPEG Compression
- 30 FPS Recording and Live
- True WDR 120dB
- SD Slot for Local Storage: Up to 128GB
- Audio Input: Built-in Mic
- IP67 Weatherproof
- IK10 Vandal Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)

Ordering Information

PAR-P4DRIR28-AI: 2 Megapixel Dome, 2.8mm

Camera	PAR-P4DRIR28-AI
Image Sensor	1 / 3 "CMOS
Image Size	2592 × 1520
Electronic Shutter	1 / 30 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.005 lux@F1.6, AGC ON; 0 lux with IR 0.0028 lux@F1.2, AGC ON; 0 lux with IR
Lens	2.8 mm @F1.6, horizontal field of view: 100.4°
Lens Mount	M12
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan : 0°~355°, Tilt : 0°~67°, Rotation : 0°~355°
Image	
Video Compression	Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	4MP (2592 × 1520), 2K (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream	4MP/2K/3MP/1080P / 720P(60Hz : 1 ~ 30fps; 50Hz: 1~25fps) HFR mode: 1080P / 720P(60Hz : 1 ~ 60fps; 50Hz: 1~50fps)
Sub Stream	720P/D1/CIF (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)
Third Stream	D1/CIF/480x240 (60Hz : 1 ~ 30fps; 50Hz: 1~25fps)
Bit Rate	64 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Simultaneous Live View	10
User/Host	Up to 16 Users, 3-Levels, Admin/Advance/Common
Alarm	1CH alarm input; 1CH alarm output
Audio	1CH audio input; 1 CH built-in MIC
Storage	Built-in micro SD card slot; up to 128GB
Hardware Reset	Yes
Functions	
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF / API / SDK
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SD card error, SD card full, IP address conflict, cable disconnection
Intelligent Analytics	Object abandoned/missing detection, region entrance/exiting/Intrusion detection(human/vehicle classification), line crossing detection(human/ vehicle classification), video tampering detection, scene change detection, face detection, face capture, crowd density detection, human/vehicle counting
General function	Watermark, IP address filtering, video mask, heartbeat, password protection, non-photosensitive switch, image distortion correction
PoE	Yes, IEEE802.3af
IR Distance	65 Feet
Protection Grade	IP67 & IK10
Other	
Power Supply	DC12V/PoE
Power Consumption	< 7W
Operating Environment	-22°F~140°F, (- 30 °C ~ 60 °C) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 4.69 x 3.46" (Φ 119 × 87.8mm)
Weight (net)	Approx. 1.43lb (0.65KG)