



PAR-P5DRIRN

5 Megapixel IP Plug & Play, Outdoor Vandal Dome, 98' EXIR Range, CVBS Output, WDR, Built-in Mic, Audio Input, SD Card Slot, 12VDC/PoE, Facial Rec

Features

- 5 Megapixel Resolution
- Fixed Lens
- Facial Recognition Capable with Compatible NVR
- True Day/Night with IR Range up to 98'
- H.265/H.264/MJPEG Compression
- 30 FPS Recording and Live
- True WDR 120dB
- Smart Analytics
- CVBS Video Output
- SD Slot for Local Storage: Up to 128GB
- Audio Input: Built-in Mic
- IP67 Weatherproof
- IK10 Vandal Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Camera	PAR-P5DRIRN
Image Sensor	1 / 2.5 "CMOS
Image Size	2592x1944
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.036 lux @F2.0, AGC ON; 0 lux with IR, 0.013 lux @F1.2, AGC ON; 0 lux with IR
Lens	2.8 mm @F1.85, horizontal field of view: 101°, 3.6 mm @F1.6, horizontal field of view: 79°
Lens Mount	M12
Day & Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Digital NR	2D / 3D DNR
Angle Adjustment	Pan : 0°~355°, Tilt : 0°~67°, Rotation : 0°~355°
Image	
Video Compression	H.265 / H.264 / MJPEG
H.265 Compression Standard	Main Profile @Leve4.1 High Tier
Resolution	5MP (2592 x 1944), 4MP (2592 x 1520), 2K (2560 x 1440), 3MP (2304 x 1296), 1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Main Stream	
Bit Rate	128 Kbps ~ 10 Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
Audio Compression	G711A / U
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Audio	MIC IN x 1, Built-in Mic
Video Output	CVBS video output (BNC x 1)
Storage	Built-in micro SD card slot; up to 128GB
Functions	
Remote Monitoring	IE browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission
Network Protocol	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network remote storage; local storage
Smart Alarm	Motion alarm
Smart Analysis	Yes
IR Distance	98 Feet
Ingress Protection	IP67
Vandal Resistant	IK10
Others	
Power Supply	DC12V/PoE
Power Consumption	< 9W
Operating Environment	-22°F ~ 140°F (-30 °C ~ 60 °C), humidity: <95 % (non-condensing)
Dimensions (mm)	Φ 4.69 x 3.46" (Φ 119 x 87.8)

Ordering Information

PAR-P5DRIR28N: 5 Megapixel Vandal Dome, 2.8mm

PAR-P5DRIR36N: 5 Megapixel Vandal Dome, 3.6mm