



## ULT-P8PANMULTI

8 Megapixel IP Plug & Play, Outdoor Multi-Camera Dome, 4 Individual Cameras with 6mm Lenses, D-WDR, Audio Input & Output, SD Card Slot, PoE/DC12V

### Features

- 8 Megapixel Resolution
- 4 Individual 6mm Lenses
- H.265+/H.265/H.264+/H.264/MJPEG Compression
- D-WDR
- 60' IR Range
- Audio Input/Output
- IP67 Weatherproof
- SD/SDHC/SDXC Card slot up to 128 GB
- 12VDC/PoE Operation
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Mac Client

|                         |   |
|-------------------------|---|
| Model Number            | ULT-P8PANMULTI  |
| Image Sensor            | 1/2.8" Progressive Scan CMOS  |
| Min. Illumination       | Color: 0.003 Lux @ F1.2, 0 Lux with IR  |
| Shutter Speed           | 1/25s – 1/100,000s  |
| Day & Night             | IR Cut Filter   |
| Digital Noise Reduction | 3D DNR  |
| WDR                     | DWDR  |
| 2-Axis Adjustment       | Pan: 0° to 355°, tilt: 0° to 90°  |
| Lens                    | 4 x 6mm lens  |
| Aperture                | F2.0  |
| FOV                     | Horizontal field of view: 180°, Vertical field of view: 30.3°   |
| IR Range                | 4 x IR LEDs, up to 60ft.  |
| Wave Length             | 850nm   |
| Video Compression       | H.265+ / H.265 / H.264+ / H.264 / MJPEG   |
| Video Bit Rate          | 32 Kbps to 16 Mbps  |
| Audio Compression       | G.711/G.722.1/G.726/MP2L2/PCM/AAC   |
| Audio Bit Rate          | 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)   |
| Behavior Analysis       | Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection |
| Max. Resolution         | 7008 x 1080   |
| Frame Rate              | 30fps @ 7008 x 1080   |
| Audio I/O               | 1/1   |
| Alarm I/O               | 1/1   |
| On Board Storage        | Built-in Micro SD/SDHC/SDXC slot, up to 128 GB  |
| Communication Interface | 1 RJ45 10M/100M/1000M Ethernet port,<br>1 RS-485 interface (-S)   |
| Fiber optic interface   | FC interface  |
| Protection Level        | IP67  |
| Power Supply            | 12 VDC ± 20%, three-core terminal block, PoE: 802.3at, class 4  |
| Power Consumption       | Max. 18W  |
| Working Temperature     | -40°F to 140°F (-40°C to 60°C)  |
| Dimensions              | 7.5" x 8.2" x 8.2"  |
| Weight                  | 7.7lbs  |

### Ordering Information

**ULT-P8PANMULTI:** 8 Megapixel Panoramic Dome