



VIS-P5DIPTZXIRA27135W

5MP, Starlight Illumination, Motorized Auto-Focus 2.7-13.5mm Lens, Indoor Only, Micro SD Slot: Up to 256GB, 12VDC/PoE Operation

Features

- 5 Megapixel Resolution
- Motorized Auto-Focus 2.7-13.5mm Lens
- True Day/Night with IR Range up to 30'
- Smart IRs
- Starlight Illumination
- Ultra H.265/H.265/H.264/MJPEG Compression
- 30 FPS Recording and Live
- True WDR 120dB
- Smart Analytics
- Micro SD Slot: Up to 256GB
- Audio Input: Built-in Mic
- Audio Output: Built-in Speaker
- Indoor Only
- 12VDC/PoE Operation
- ONVIF
- WiFi Compatible- 2.4Ghz Only
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Model	VIS-P5DIPTZXIRA27135W
Sensor	1/2.7" progressive, scan, 5.0 megapixel, CMOS
Lens	2.7~13.5mm, AF automatic focusing and motorized zoom lens
DORI Distance	2.7mm: 60.8 m (Detect) 24.3 m (Observe) 12.2 m (Recognize) 6.1m (Identify) 13.5mm: 303.8 m (Detect) 121.5 m (Observe) 60.8 m (Recognize) 30.4m (Identify)
Angle of View (H)	27.9°~98.3°
Angle of View (V)	20.6°~70.3°
Angle of View (O)	30.0°~136.9°
Shutter	Auto/Manual, shutter time: 1 s ~ 1/100000 s
Minimum Illumination	Colour: 0.002 lux (F1.2,AGC ON) 0 lux with IR
Iris	F1.2
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>55 dB
IR Range	UP to 30m (98ft)
WDR	120dB
Video	
Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:5M (2592*1944):Max. 30 fps; Sub Stream: 720P (1280*720):Max. 30 fps; Third Stream: D1 (720*576): Max. 30 fps
BLC	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 24 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Smart	
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8 KHZ
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL
Compatible Integration	ONVIF(Profile S, Profile G), API
Pan & Tilt	
Pan Range	350°
Pan Speed	0.1°/s ~ 60°/s
Preset speed: 60°/s	
Tilt Range	0° ~ 90°
Tilt Speed	0.1° ~ 50°/s
Preset speed: 50°/s	
Number of Presets	1024
Home Position	Supported
Interface	
Alarm I/O	43831
Serial Port	1 RS485
Network	1 RJ45 10M/100M Base-TX Ethernet
Built-in Mic	Supported
Built-in Speaker	Supported
WIFI	Supported-2.4Ghz Only
General	
Power	DC 12V±25%, PoE (IEEE802.3 at) Power consumption: Max 16W
Dimensions (Ø x H)	Ø 5.07 x 5.63 (129mm×143mm)
Weight	1.65lb (0.75kg)
Working Environment	14°F ~ 122°F (-10°C ~ +50°C), Humidity:≤95% RH(non-condensing)
Reset Button	Supported

Ordering Information

VIS-P5DIPTZXIRA27135W:

5 Megapixel Resolution, Motorized Auto-Focus 2.7-13.5mm Lens