



ELEVI-C5TXIR

5-2 Megapixel Field Selectable TVI/AHD/CVI/CVBS,
Outdoor Turret, 65' IR Range, D-WDR, up to -40, 12VDC

Features

- 5-2 Megapixel Field Selectable**
- All-in-One Technology (TVI/AHD/CVI/Analog 960h)
- Fixed Lens
- True Day/Night
- D-WDR
- 65' Smart IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- 12VDC Only Operation
- Through InVid Tech DVR:
Free App, CMS & MAC Client

Model	ELEVI-C5TXIR
Image Sensor	1/2.5" CMOS Sensor
Signal System	NTSC/PAL
Effective Pixels	2592(H) x 1944(V)
Field of View	Horizontal: 102° Vertical:74°
Electronic Shutter	AUTO/ 1/50 1/60 -1/50,000sec
Min. Illumination	0.01Lux
Video Output	"TVI:5MP 20/12.5 FPS, 4MP 30/25/12.5 FPS, 2MP 30/25 FPS AHD:5MP 20/12.5 FPS, 4 MP 30/25 FPS, 2MP 30/25 FPS CVI:4MP 30/25 FPS, 2 MP 30/25 FPS CVBS"
Video Output By Default	"TVI: 5MP @ 20 FPS AHD:2MP @ 30 FPS CVI: 2MP @ 30 FPS CVBS"
Dip Switch	Support
UTC Control	Support
Camera Features	
Mirror Image	Yes
Auto Iris	No
Sharpness	Yes
Defogging	No
BLC	Yes
D-WDR	Yes
S/N Ratio	>41dB
Noise Reduction	2DNR
Day&Night	Color / B&W/ AUTO / EXT
White Balance	Manual/Auto
AGC	Auto
IR LED	18pcs SMD IR
IR Range	Up to 65 ft
Lens	
Focal Length	2.8mm Fixed Lens
Lens Type	Fixed Iris
Mount Type	M12
General	
IP Rating	IP66
Casing	Metal
Power Supply	DC12V(+/-10%)
Power Consumption	IR OFF:85mA / IR ON:320mA
Working Temperature / Humidity	-40°F-140°F(-40~+60°C)
Dimensions(WxDxH)	4.00" x 3.52"
Weight	.82 lbs (370g)

Ordering Information

ELEVI-C5TXIR28: 5-2 Megapixel Turret, 2.8mm

**Scale down to other resolutions via camera dip switches & OSD

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.