



ELEVI-P5BXIR28

5 Megapixel IP Plug & Play, Outdoor Mini Bullet,
98' IR Range, WDR, PoE/DC12V

Features

- 5 Megapixel (2592x1944)
- Fixed Lens
- H.265/H.264
- True Day/Night
- True WDR 120dB
- Smart IR Range up to 98'
- IP66 Weather Resistant
- 12VDC/PoE Operation
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC client

Model	ELEVI-P5BXIR28
Sensor+DSP	IMX335+Hi3516EV300
Sensor	1/2.8" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color), 0lux(IR on)
Lens	2.8 mm@F1.85: horizontal FOV: 99°, vertical FOV:56°
Lens Mount	M12
IR	14milX18pcs SMD LED
IR Range	98ft (30m)
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR&D&WDR (13fps)
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.265
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Image	
Max. Image Resolution	5MP(2592 × 1944)(default 15fps)
Frame Rate	50Hz: 15fps 5MP (2592 × 1944) 15fps 4MP (2560 × 1440), 15fps 4MP(2304 × 1728) 25fps 3MP (2048 × 1536), 25fps 1080P(1920 × 1080) 25fps 960P (1280 × 960), 60Hz: 15fps 5MP (2592 × 1944) 15fps 4MP (2560 × 1440), 15fps 4MP(2304 × 1728) 30fps 3MP (2048 × 1536), 30fps 1080P(1920 × 1080) 30fps 960P (1280 × 960), 30fps 720P(1280 × 720)
Sub Stream	50Hz: 25fps 720P(1280 × 720) 25fps D1(704 × 576), 25fps CIF(352 × 288) 60Hz: 30fps 720P(1280 × 720) 30fps D1(704 × 480), 30fps CIF(352 × 240)
Third Stream	N/A
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	N/A
Protocols	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPv6
Event	Motion Detection, Video Shelter
Smart Functions	Line Crossing, Area Intrusion, Region Entrance, Region Exiting, Fast Moving, Face Detection
System compatibility	CGI
Security	User authentication, IP address filtering, Video mask
Mobile Surveillance	iPhone, iPad, Android, CMS, WEB
Interface	
Communication interface	1 RJ45 10M / 100M/ Ethernet Port
General	
Operating Conditions	-22°F ~ 140°F (-30°C ~ 60°C) Humidity 95% or less (non-condensing) "
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 8.5W
Weather Proof	IP66
Dimensions	2.65 x 2.26 x 5.98 inches (67.5X57.5X152mm)
Weight	0.80lb (365g)

Ordering Information

ELEVI-P5BXIR28: 5 Megapixel Bullet, Fixed Lens

Made in Indonesia

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.