



## ELEVI-P5DRXIR

5 Megapixel IP Plug & Play, Outdoor Dome, 98' IR Range, WDR, Built-in Mic, SD Card Slot, PoE/DC12V

### Features

- 5 Megapixel (2592x1944)
- Fixed Lens
- H.265/H.264
- True Day/Night
- True WDR 120dB
- Smart IR Range up to 98'
- TF Card Local Storage, 128GB
- Built-In Mic
- IP66 Weather Resistant
- IK10 Vandal Resistant
- 12VDC/PoE Operation
- ONVIF
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Model	ELEVI-P5DRXIR28
Sensor+DSP	IMX335+Hi3516EV300
Sensor	1/2.8" Progressive scan CMOS Sensor
Min. Illumination	0.01lux (Color), 0 lux (IR on)
Lens	3.6 mm@F2.0: horizontal FOV: 85°, vertical FOV:44°
Lens Mount	M12
IR	9miX18pcs SMD LED
IR Range	98 ft. (30m)
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR & DWDR (13fps)
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.265
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~10 Mbps
Audio Compression	G.711A, G.711U
Audio Bit Rate	64 Kbps
Image	
Max. Image Resolution	5MP(2592 × 1944) (default 15fps)
Frame Rate	50Hz:15fps 5MP(2592 × 1944) 15fps 4MP(2560 × 1440),15fps 4MP(2304 × 1728) 25fps 3MP(2048 × 1536),25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 60Hz:15fps 5MP(2592 × 1944) 15fps 4MP(2560 × 1440),15fps 4MP(2304 × 1728) 30fps 3MP(2048 × 1536),30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960),30fps 720P(1280 × 720)
Sub Stream	50Hz:25fps 720P(1280 × 720) 25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz:30fps 720P(1280 × 720) 30fps D1(704 × 480),30fps CIF(352 × 240)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Protocols	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour,IPv6, FTP
Event	Motion Detection, Video Shelter
Smart Functions	Line Crossing, Area Intrusion, Region Entrance, Region Exiting, Fast Moving, Face Detection
System compatibility	Onvif(Profile S), CGI
Security	User authentication,IP address filtering,Video mask
Mobile Surveillance	iPhone, iPad, Android , CMS, WEB
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
On-board Storage	Built-in Micro SD/SDHC/SDXC slot up to 128GB
MIC	Support
General	
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 8.5W
Weather Proof	IP66
Vandalproof	IK10
Dimensions	Ø 100.6x 88.5(H) mm
Weight	540g(1.19lb)

### Ordering Information

**ELEVI-P5DRXIR28:** 5 Megapixel Dome, 2.8mm

### Made in Indonesia

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.