



VIS-P5DIPTZXIRA27135

5MP, Starlight Illumination, Motorized Auto-Focus 2.7-13.5mm Lens, Indoor Only, Micro SD Slot: Up to 256GB, 12VDC/PoE Operation, Two Way Audio Built in

Features

- 5 Megapixel Resolution
- Motorized Auto-Focus 2.7-13.5mm Lens
- True Day/Night with IR Range up to 98ft
- Smart IRs
- Starlight Illumination
- Ultra H.265/H.265/H.264/MJPEG Compression
- 30 FPS Recording and Live
- True WDR 120dB
- Smart Analytics
- Micro SD Slot: Up to 256GB
- Audio Input: Built-in Mic
- Audio Output: Built-in Speaker
- Indoor Only
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS)
- Free MAC Client

Model	VIS-P5DIPTZXIRA27135
Sensor	1/2.7" progressive, scan, 5.0 megapixel, CMOS
Lens	2.7~13.5mm, AF automatic focusing and motorized zoom lens
DORI Distance	2.7mm: 60.8 m (Detect) 24.3 m (Observe) 12.2 m (Recognize) 6.1m (Identify)
	13.5mm: 303.8 m (Detect) 121.5 m (Observe) 60.8 m (Recognize) 30.4m (Identify)
Angle of View (H)	27.9°~98.3°
Angle of View (V)	20.6°~70.3°
Angle of View (O)	30.0°~136.9°
Shutter	Auto/Manual, shutter time: 1 s ~ 1/100000 s
Minimum Illumination	Colour: 0.002 lux (F1.2,AGC ON) 0 lux with IR
Iris	F1.2
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>55 dB
IR Range	UP to 30m (98ft)
WDR	120dB
Video	
Video Compression	Ultra 265,H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile, High Profile
Frame Rate	Main Stream:5M (2592*1944):Max. 30 fps;
	Sub Stream: 720P (1280*720):Max. 30 fps;
	Third Stream: D1 (720*576): Max. 30 fps
BLC	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 24 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Smart	
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711
Suppression	Supported
Sampling Rate	8 KHZ
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP , PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP , 802.1x , SNMP, SSL
Compatible Integration	ONVIF(Profile S, Profile G) , API
Pan & Tilt	
Pan Range	350°
Pan Speed	0.1°/s ~ 60°/s
Preset speed: 60°/s	
Tilt Range	0° ~ 90°
Tilt Speed	0.1° ~ 50°/s
Preset speed: 50°/s	
Number of Presets	1024
Home Position	Supported
Interface	
Alarm I/O	43831
Serial Port	1 RS485
Network	1 RJ45 10M/100M Base-TX Ethernet
Built-in Mic	Supported
Built-in Speaker	Supported
General	
Power	DC 12V±25%, PoE (IEEE802.3 at) Power consumption: Max 16W
Dimensions (Ø x H)	Ø 5.07 x 5.63 (129mm×143mm)
Weight	1.65lb (0.75kg)
Working Environment	14°F ~ 122°F (-10°C ~ +50°C), Humidity:≤95% RH(non-condensing)
Reset Button	Supported

Ordering Information

VIS-P5DIPTZXIRA27135:

5 Megapixel Resolution, Motorized Auto-Focus 2.7-13.5mm Lens