



VIS-P8PTZXIR22

8 Megapixel IP, Outdoor PTZ, 22x, 820' EXIR Range, Audio Input/Output, SD Card Slot, 24VAC, POE

Features

- 22X Optical Zoom
- Fifth-generation infrared technology, more than 250m (656ft) IR distance
- IR anti-reflection window to increase the infrared transmittance
- Optical glass window with higher light transmittance
- Smart IR
- EIS (Electronic Image Stabilization)
- 8 Megapixel image
- Ultra 265,H.265, H.264, MJPEG
- 24 V AC±25% (Default), 24 V DC±25%
- Power consumption: 16 W ~ 56 W, PoE (PSE Required, sold separately)
- Embedded smart algorithm
- Triple streams
- Customized OSD
- ONVIF Conformance
- Innovative snow-removing functionality
- Intelligent temperature control technology
- More effective heat dissipation system

Camera	VIS-P8PTZXIR22
Sensor	1/1.7" progressive scan, 12.0 megapixel, CMOS
Lens	6.5~ 143 mm
Digital Zoom	16
Optical Zoom	22
DORI Distance	Lens: 6mm, Detect: 158.1m, Observe: 63.2m, Recognize: 31.6m, Identify: 15.8m Lens: 143mm, Detect: 3478.4m, Observe: 1391.4m, Recognition: 695.7m, Identify: 347.8m
Angle of View (H)	56.69°~3.19°
Angle of View (V)	34.2°~1.6°
Angle of View (O)	69.7°~3.7°
Shutter	Auto/Manual, shutter time: 1s ~ 1/100000 s
Minimum Illumination	Colour: 0.01 lux (F1.5,AGC ON), 0 lux with IR
Iris	Auto/Manual, F1.5 ~ F3.4
Day/Night	IR-cut filter with auto switch (ICR)
Digital noise reduction	2D/3D DNR
S/N	>55 dB
IR Range	UP to 250m (820ft)
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265,H.265, H.264, MJPEG
Frame Rate	Main Stream: 12 MP(4000×3000):Max.20 fps, 8MP(3840 × 2160): Max.25fps, 2MP(1920×1080)@30fps, Sub Stream:2MP(1920×1080) : Max. 30fps, Third Stream: D1 (720×576): Max. 30fps
HLC	Supported
BLC	Supported
EIS	Supported
ROI	Up to 8 areas
OSD	Up to 8 OSDs
Privacy Mask	Up to 24 areas
Motion Detection	Up to 4 areas
SMART	
Behavior Detection	Intrusion, cross line, motion detection
Intrusion	Enter and loiter in a pre-defined virtual region
cross line	Cross a pre-defined virtual line
Motion detection	Moving within a pre-defined virtual region
Recognition	Face detection, Audio detection
Intelligent Identification	Defocus, Scene Change, Object Left, Object Moving
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8 KHZ
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S, Profile G, Profile T), API
Pan & Tilt	
Pan Range	360°
Pan Speed	0.1°/s ~ 240°/s, Preset speed: 300°/s
Tilt Range	-15° ~ +90° (auto reverse)
Tilt Speed	0.1° ~ 160°/s Preset speed: 240°/s
Number Of Presets	1024
Patrol	Preset patrol, route patrol, recorded patrol
Home position	Supported
Interface	
Audio I/O	Audio cable 1 Input: impedance 35 kΩ; amplitude 2 V (p-p) 1 Output: impedance 600 Ω; amplitude 2 V (p-p)
Alarm I/O	2 / 1
Serial Port	1 RS485
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V (p-p)
General	
Power	24 V AC±25% (Default), 24 V DC±25% Power consumption: 16 W ~ 56 W, PoE (PSE Required, sold separately)
Dimensions	φ270mm×496.7mm(φ10.6" × 19.6")
Weight	9.69kg(21.4lb)
Working Environment	-40°C ~ +70°C (-40°F ~ 158°F), Humidity: 10%~ 95% RH(non-condensing)
Ingress Protection	IP66

Ordering Information

VIS-P8PTZXIR22: 8 Megapixel PTZ

InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.