




PRO10TM UPGRADE

“Building the best, servicing the rest”TM



DESIGN FEATURES & BENEFITS

- 0.7mm thickness - reduced bending and increased durability
- Bright annealed finish - allows for better evaluation of CIP response
- Improved inlet design - ideal for viscous products
- Enlarged hanger - allows plates to slide smoothly during installation or inspection
- Snap-in Gasket - provides secure gasket attachment

AGC ADVANTAGES

- Pro10 has existing AGC ProFlow design features & improved thermal performance
- For new AGC frames and upgrade for Clip10, Front10 and C10 frames without piping changes
- Plates packed in order per streaming diagram
- In stock and ready to ship - minimal lead time
- Onsite installation service available



PRO10™

AGC Pro10™ enlarged hanger design

Old style hanger offers little clearance

AGC Pro10™ ENLARGED HANGER allows plates to slide smoothly during installation or inspection


Old style restricted inlet design

AGC Pro10™ free-flow inlet design

AGC Pro10™ ENLARGED OPENING provides lower pressure drop in the port inlet



SNAP-IN GASKET provides secure gasket attachment



METAL TO METAL ALIGNMENT device and reinforced side band

ASK ABOUT OUR PRO10™ TIE-BOLT AND TWIN SPINDLE AUTO CLOSE FRAMES!

GENERAL INFORMATION

Plate and Gasket Weight:	Stainless Steel 9.74 lbs / 4.42kg Hastelloy 8.41 lbs / 3.81 kg
Heat Transfer Area:	6.67 ft ² / 62m ²
Plate Thickness:	0.7mm Stainless Steel 0.6mm Hastelloy
Volume (per channel):	0.64 gallons / 2.4L
Gasket Options:	Nitrile (NBR), EPDM



Western

3109 NE 230th Avenue
Fairview, OR 97024
+1.503.774.7342
+1.800.715.8820
FAX +1.503.774.2550

Central

8400 Lakeview Parkway
Suite 700
Pleasant Prairie, WI 53158
+1.847.301.6890
+1.888.489.8820

Eastern

10129 Piper Lane
Bristow, VA 20136
+1.703.257.1660
+1.800.825.8820
FAX +1.703.330.7940

proflow sanitary
S E R I E S

See us on the web at www.agcheattransfer.com