

| Job: | |
|------|--|
| | |

Item No.

Designed For High Volume ApplicationsReduces Noise and Work Area Heat Build-up

The **SaniServ** Model ROC2361 (by Copeland®) Remote Condensing Unit, can be used with any **SaniServ** remote ready dispensing unit.

ROC2361 Remote Condensing Unit

Unit includes:

- Outdoor rated, 2 HP condenser
- · Galvanized all-weather enclosure
- Contactor mounted and wired
- High and low pressure controls mounted and wired separately
- Immersion type crankcase heater

Optional:

• 25', 50' and 75' pre-charged lines available



We reserve the right to change specifications and product designs without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.





Mechanical

| Unit Height (in): | 19.0 | |
|------------------------------------|-------|--|
| Unit Length (in): | 25.2 | |
| Unit Width (in): | 34.1 | |
| Ship Weight (lbs): | 194.0 | |
| Condensor Type: | Air | |
| Cope∀ap Water Storage: | NA | |
| Liquid Connection Size (in)/Type: | 3/8 S | |
| Suction Connection Size (in)/Type: | 7/8 S | |
| Discharge Line Size(in): | 0.5 | |
| Water Inlet (in): | | |
| Water Outlet (in): | | |
| Oil Type: | POE | |
| Oil Recharge Amount (oz): | 25 | |

Electrical

| Max Fuse Size: | 35 |
|---|-----------------|
| Min Circuit Ampacity: | 22.4 |
| Compressor: | ZS15KAE-PFV-118 |
| Compressor LRA - Low: | |
| Compressor LRA - High: Compressor LRA - Half winding: | 68.0 |
| Compressor RLA: | 15.7 |
| UL: | |
| UL File #: | |
| UL Guide Card: | |
| Amps Per Motor: | |
| Fan Motor Quantity: | 2 |