
TEMPERATURE DATA MONITORING













Built-in USB Connector Directly plug into PC, No cable required



Integrated PDF generating Software on-board, no software required



IP67 Protection class Foodsafety and water-proof packaging



Qualified for Air Transport Monitoring Complies to RTCA/DO-160G Environmental Conditions, qualified for air transport under active status.



GDP compliant











Using Plustrace G1-







O2 Put the started logger G1 to anywhere of your shipment



O3 Connect to PC USB port



04 Directly get the pdf report automatically

SPECIFICATION

Data logger type:	Single-Use data logger
Temperature range:	-30°C to +70°C (-22°F to 158°F)
Accuracy:	±0.5°C/0.9°F (-20°C/+40°C) otherwise ±1.0
Resolution:	0.1°C/°F
Storage capacity:	32000 Measurements
Life/Battery:	20 months/CR2032 button cell battery
Measurement interval:	5 minutes (standard – other options on request)
Recording time:	90 days (standard – other options on request)
Startup method:	Push Start
Stop method:	Push stop or automatic stop when plug into PC.
Alarm type:	Single or cumulative – Up to 5 points
Protection class:	IPE67/NEMA 6
Dimensions:	76mm x 31mm x 4.5mm [L x W x H]
Weight:	Approx 15g
Certified:	EN12830, CE, RoHS NIST
Calibration certificate:	Nvlap NIST traceable (United States)
Software:	Self-generated, no software required
Report:	Adobe PDF graphics
Automatic report:	PDF
PC connection:	USB2.0
Delivery contents:	Dispatch documents, certificate



Tel: +44 (0)1722 429 594

Mail: sales@cargo-wise.co.uk

