

PULPWOOD SPECIFICATIONS

Revised 1/9/19

SPECIES ACCEPTED

- 1. HARDWOOD All deciduous species **except willow**.
- 2. PINE All coniferous species except red cedar.

LENGTHS

Wood will be received in random lengths in two basic classes.

Class Length 8' - 15'

- 1. Length classes must not be mixed within the same rank.
- 2. Wood must not be double-ended within the same rank (example: two 9' pieces making an 18')

THE FOLLOWING WILL NOT BE ACCEPTED:

- 1) Wood **smaller than 4**" in diameter.
- 2) Wood shorter than 8' in length.
- 3) Wood <u>larger than 24"</u> in diameter at any point on the log.
- 4) Wood with sweep or crook exceeding 24".
- 5) Willow or red cedar wood.
- 6) Fire-charred wood.
- 7) Wood containing metal.
- 8) Improperly trimmed wood.
 - a. Wood must be saw cut on both ends.
 - b. Knots and limbs must be cut flush with the stem.
- 9) Wood with any splitting, shattering or splintering of any type or length.
- 10) Wood with hollows in excess of 25% of the diameter that the hollow extends more than 2' into the log.
- 11) Rotten, decayed, or unsound wood.
- 12) Wood delivered without proper authorization.
- 13) Loads with mud, stones, trash or plastic, including plastic flagging on trees.

TRUCK LOADING AND RIGGING

- 1. Rigging and loading method must be approved by a Pixelle representative prior to the initial delivery.
- 2. All trucks must have a minimum of 60" between standards supporting any rank of wood.
- 3. Standards must be placed so the unloader can grasp the rank near the balance point.
- 4. Trucks must have risers of 6" above the truck bed.
- 5. Wood must not be interlocked between ranks or sticking through the head gate.
- 6. Pine and hardwood must not be mixed in the same rank.
- 7. Pixelle is not liable for any damage to trucks caused by wood falling from mixed classes or improper loading of trucks.