

O3 PRODUCTS

TRENCH GRATES

General Information	23
Slotted	25
High Performance	31
Ready-Cut	35
Pattern	37
Avant-Garde	39
Nature	41
Modern	43

Trench Grates

Optional Features and Accessories

Jonite reinforced stone trench grates add a gloss of natural, yet modern finish that complements any city hardscape. The humble drain can now be elevated to match any design style.






Heel-Guard™ Grates

Heel-Guard™ Grates have slim 6mm slots and small radius fillets to prevent high heels from being caught in the grates. Compliant with Americans with Disabilities Act (ADA) requirements, these are extremely useful for cut-off or scupper drains of the entrance or concourse areas of a building.



Grate Tiles $^{\text{m}}$ are standard non-perforated solid slabs that have the same material composition and colour as Jonite grates. They are mainly used when a drain encounters an irregular joint or to fill an odd end of a drain.



L-Trimmers™

L-Trimmers™ is recommended for gratings built for heavy-duty applications and above. They are designed to provide aesthetic flair as well as the ideal support for all Jonite grates.



Custom Curve Grates

23

Curve grates are available in any radius and design upon request. All radius in a plan will be consolidated in a full-scale CAD drawing to help minimise the number of custom toolings required.

GENERAL SPECIFICATIONS

A fundamental hardscape design element of any modern city is the drainage system, which protects against flooding by draining excess water away.

Now, underground drainage systems are designed to cope with frequent storms where any excess water always travels along the planned drainage flow paths to prevent flooding. Drainage systems are carefully planned to factor in the impact the drainage system has on our natural rivers and creeks. We are preventing waste from being washed into rivers and seas.

At Jonite, our reinforced stone channel grates and trench grates have redefined the role of gratings and drain covers in the architecture industry. With Jonite channel gratings and trench gratings, outdoor drain covers are more than functional products – they become a cornerstone in your design. They can become design focal points, inviting the viewer's eye to follow intricate patterns that open up into the building design.

All products in Jonite trench grates collection are available in exquisite textures and colours. All its trench grates give you the finish of natural stone with the strength to sustain pedestrian and vehicular load performance and durability for a lifetime.

Jonite absorbs much less heat compared to traditional ferrous gratings, making it a more comfortable material to have around the house and in children's playgrounds. Also, it has dielectric properties equivalent to porcelain, making it an excellent electrical insulator- a significant plus point in times of tropical thunderstorms.

Landscape architects like yourself have used our channel and trench grates for a variety of purposes, such as outdoor drain covers, channel grating along driveways, storm drainage and indoor applications. Aesthetics and functionality in a perfect marriage culminating in Jonite products makes us the natural choice.

PRODUCT SPECIFICATIONS

√

Slip-resistant

Rust & corrosion-resistant

BS EN 124:2015 & 1433:2008 compliant

Dielectric properties with excellent electric insulator

Less heat absorbent than traditional ferrous grates

LEED® (Leadership in Energy and Environmental Design) green building certified

LOADING SPECIFICATIONS

Class A15 - Class D400









24

SLOTTED

Classic and clean-cut designs in compliance with BS EN 124:2015 that cover a wide range of openings. Suitable for various applications, from scupper indoor and outdoor drains to common house drains and wider drains in parks, commercial and industrial surroundings.





31110

S1-125H25LD

Load class A15

Drain width 75 to 90mm

Dimension 125W x 500L x 25mm (t)



31111

S1-125H25HD

Load class B125

Drain width 75 to 85mm

Dimension 125W x 500L x 25mm (t)



31112

C1-210H25LD

Load class A15

Drain width 128 to 170mm

Dimension 210W x 500L x25mm (t)



31113

C1-210H35HD

Load class B125

Drain width 128 to 160mm

Dimension 210W x 500L x 35mm (t)



31114

C2-292H25LD

Load class A15
Drain width 210

210 to 242mm

Dimension 292W x 500L x 25mm (t)



31115

Load class

C2-292H35HD B125

Drain width 210 to 232mm

Dimension 292W x 500L x 35mm (t)



31116

Load class A15

Drain width 273 to 305mm

Dimension 355W x 500L x 25mm (t)



31117

C3-355H35HD

C3-355H25LD

Load class B125

Drain width 273 to 295mm

Dimension 355W x 500L x 35mm (t)



31118

C4-435H35LD

Load class

Drain width 345 to 385mm

Dimension

435W x 420L x 35mm (t)



31119

C4-435H50HD

B125 Load class

345 to 375mm Drain width

435W x 420L x 50mm (t) Dimension



31120

C5-500H35LD

A15 Load class

Drain width

400 to 450mm

500W x 365L x 35mm (t) Dimension

B125



31121

C5-500H50HD

Load class

Drain width

400 to 440mm

Dimension 500W x 365L x 50mm (t)



34119C

Load class

Suitable for

90° S1-H25LD

Standard S1-125H25LD



34120C

Load class B125

Suitable for

Standard S1-125H25HD

90° S1-H25HD



34110C

90° C1-H25LD

Load class

Suitable for

Standard C1-210H25LD



34111C

90° C1-H35HD

Load class

B125 Suitable for Standard C1-210H35HD



34113C

90° C2-H25LD

Load class

A15

Standard C2-292H25LD Suitable for



34114C

Suitable for

90° C2-H35HD

Load class

B125

Standard C2-292H35HD



34116C

Suitable for

90° C3-H25LD

Load class

A15

Standard C3-355H25LD



34117C

Load class

Suitable for

Standard C3-355H35HD

90° C3-H35HD



34133C

90° C4-H35LD

Load class

Suitable for Standard C4-435H35LD

A15

B125



34134C

90° C4-H50HD

Load class

Suitable for

Standard C4-435H50HD

A15





34135C

90° C5-H35LD

Load class A15

Suitable for

Standard C5-500H35LD



34136C

90° C5-H50HD

Load class B125

Suitable for Standard C5-500H50HD



34121C Dimension L-TRIMMER-25LD

60W x 500L x 35mm (t)



34122C Dimension L-TRIMMER-35HD/EHD

60W x 500L x 50mm (t)



34126C

L-SLIM-TRIMMER-25LD/HD

Dimension 40W x 500L x 35mm (t)



34127C Dimension TS-50-LD (Tile-Strip)

50W x 500L x 10mm (t)



34129C

GT-400H25LD (Grate-Tile)

Load class

Dimension

400W x 400L x 25mm (t)



34131C

GT-400H35HD (Grate-Tile)

Load class

Dimension 400W x 400L x 35mm (t)



34130C

GT-500H25LD (Grate-Tile)

Load class

A15

Dimension 500W x 500L x 25mm (t)



34132C

GT-500H35HD (Grate-Tile)

Load class B125

Dimension

500W x 500L x 35mm (t)

TRENCH GRATES

COLLECTION

PRODUCTS \rightarrow

HIGH **PERFORMANCE**

Specially designed for heavy loading applications such as car-park entrances, hard-standing areas, driveways and kerb sides. L-Trimmers are recommended to ensure a flat and level seating of gratings.





32110

C1-210H35EHD

Load class C250

128 to 150mm Drain width

Dimension 210W x 500L x 35mm (t)



32111

C1-210H50CHD

210W x 500L x 50mm (t)

Load class D400

Drain width 128 to 150mm

Dimension

32112

C2-292H35EHD

C250 Load class

Drain width 210 to 230mm

Dimension 292W x 500L x 35mm (t)



32113

C2-292H50CHD

Load class D400

Drain width 210 to 230mm

Dimension

292W x 500L x 50mm (t)



32114

C3-355H50EHD

Load class C250

Drain width 273 to 285mm

355W x 500L x 50mm (t) Dimension



32115

Drain width

C3-355H75CHD

Load class D400

273 to 285mm

Dimension 355W x 500L x 75mm (t)



32116

C4-435H70EHD

Load class C250

Drain width 345 to 365mm Dimension 435W x 420L x 70mm (t)



32125

C4-435H75CHD D400

Load class

Drain width 345 to 365mm

Dimension 435W x 420L x 75mm (t)



32117

D1-167H35EHD

Load class C250

Drain width 100 to 117mm

Dimension

167W x 750L x 35mm (t)



32118

D1-167H50CHD


D400 Load class

Drain width 100 to 117mm

Dimension

167W x 750L x 50mm (t)

TRENCH GRATES



32121

D3-495H75EHD

Load class C250

Drain width 395 to 425mm

Dimension 495W x 370L x 75mm (t)



32122

D3-495H75CHD

D400 Load class

Drain width 395 to 425mm

495W x 370L x 75mm (t) Dimension



32123

BW1-260H50EHD

Load class C250

Drain width 200mm

260W x 500L x 50mm (t) Dimension



32124

BW2-400H50EHD

Load class Drain width

C250 330mm

Dimension

400W x 500L x 50mm (t)

90° C1-H35EHD



34112C Load class

C250

C250

C250

Suitable for

Standard C1-210H35EHD



34115C

90° C2-H35EHD

Load class

Suitable for

Standard C2-292H35EHD




34118C

90° C3-H50EHD

Load class

Suitable for

Standard C3-355H50EHD



34122C

L-TRIMMER-35HD/EHD

60W x 500L x 50mm (t) Dimension

34123C

Dimension

L-TRIMMER-50EHD/CHD

65W x 500L x 65mm (t)



34124C

L-TRIMMER-70EHD/CHD

Dimension 65W x 420L x 85mm (t)



34125C

Dimension

L-TRIMMER-75EHD/CHD

65W x 500L x 90mm (t)



34128C

Dimension

TS-50-HD/EHD (Tile-Strip)

50W x 500L x 15mm (t)

TRENCH GRATES **READY-CUT**

COLLECTION

READY-CUT

Designed for replacement purposes without any form of construction work on existing drains. The longitudinal side of the gratings has a wider edging so that they can be cut to attain the required widths.





33110

CC1-275H25LD

Load class A15

Drain width

171 to 225mm

Dimension 275W x 500L x 25mm (t)



33111

CC1-275H35HD

Load class B125

Drain width

161 to 215mm

Dimension 275W x 500L x 35mm (t)



33112

CC1-275H35EHD

Load class

C250 Drain width 161 to 205mm

275W x 500L x 35mm (t) Dimension

35



33113

CC2-330H25LD

Load class A15

Drain width 243 to 280mm

330W x 500L x 25mm (t) Dimension



33114

CC2-330H35HD B125

Load class

Drain width 233 to 270mm

Dimension 330W x 500L x 35mm (t)



33115

CC2-330H50EHD

C250 Load class

223 to 260mm Drain width

330W x 500L x 50mm (t) Dimension



33116

CC3-410H35LD

Load class

A15

Drain width 225 to 360mm

Dimension 410W x 500L x 35mm (t)



33117

CC3-410H35HD

B125 Load class

Drain width

296 to 350mm

Dimension 410W x 500L x 35mm (t)



33118

Drain width

CC3-410H50EHD C250

36

Load class

286 to 340mm

Dimension 410W x 500L x 50mm (t)

TRENCH GRATES **PATTERN**

COLLECTION

PATTERN

Creative and imaginative designs for enhanced aesthetic flair while maintaining load strength. Available in 2 standard designs: ornate Keyholes and contemporary Baby Pebbles.

U33115

MG-PEBBLES-78

6KN Load class

Drain width 52 to 54mm

78W x 610L x 21/25mm (t) Dimension

61115

BABY PEBBLES-86

Load class 6KN

Drain width 56 to 62mm

86W x 498L x 23mm (t) Dimension

61116

BABY PEBBLES-122

Load class 6KN

Drain width 80 to 100mm

Dimension 122W x 498L x 19mm (t)

U32115 TG-PEBBLES-124

Load class 6KN

Drain width 92 to 100mm

Dimension 124W x 500L x 19mm (t)

61111

BABY PEBBLES-150

150W x 500L x 25mm (t)

Load class 6KN

Drain width 100 to 125mm

61112

Dimension

BABY PEBBLES-210

6KN Load class

Drain width 160 to 170mm

Dimension 210W x 500L x 25mm (t)





61113

BABY PEBBLES-300

Load class 6KN Drain width

245 to 260mm

KEYHOLES-122

Dimension 300W x 500L x 35mm (t)

61117

Load class

A15

Drain width 92 to 100mm

Dimension 122W x 498L x 22mm (t)

U32112

Load class A15

Drain width 92 to 100mm

Dimension 124W x 500L x 22mm (t)



61118

KEYHOLES-300

TG-KEYHOLES-124

6KN Load class Drain width 250mm

Dimension

300W x 500L x 28mm (t)



AVANT-GARDE

Abstract and innovative designs reminiscent of rain motifs for a futuristic and non-traditional finish.



64115

CHISELLED-122

Load class 6KN

Drain width 92 to 100mm

Dimension 122W x 498L x 22mm (t)



U32110

O TG-CHISELLED-124

Load class A15

Drain width 92 to 100mm

Dimension 124W x 500L x 22mm (t)



64116

Load class 6KN
Drain width 250mm

Dimension 300W x 500L x 28mm (t)

RAIN-SWING-300

CHISELLED-300

Load class A15 Drain width 250mm

Dimension


64114

300W x 500L x 25mm (t)

39

NATURE

Created with floral and leaf-inspired designs for a stylish tropical resort touch, that allows the gratings to blend in more aesthetically with different landscapes and architecture.





62111 LEAVES-310

Load class 5KN

Drain width 210 to 260mm

Dimension 310W x 335L x 25mm (t)



62112 FOREST-300

Load class 5KN Drain width 250mm

300W x 500L x 25mm (t) Dimension



62113

PALM-122

Load class A15

Drain width 92 to 100mm

122W x 498L x 22mm (t) Dimension



U32114 TG-PALM-124

Load class A15

Drain width 92 to 100mm

Dimension 124W x 500L x 22mm (t)

PALM-300



62114

Load class 6KN Drain width 250mm

300W x 500L x 28mm (t) Dimension



41

42

MODERN

Minimalist and clean architectural lines feature strongly in this collection, making it the best match for modern styles. Available in 3 types of designs: Cross-Stitch, Interlace, and Square Slots.



63115

CROSS-STITCH-86

A15 Load class Drain width 60mm

Dimension 86W x 498L x 23mm (t)



63116

CROSS-STITCH-122

Load class

A15

Drain width 92 to 100mm

Dimension 122W x 498L x 19mm (t)



U32111

TG-CROSS-STITCH-124

Load class A15

Drain width

92 to 100mm

Dimension 124W x 500L x 19mm (t)



63110

CROSS-STITCH-300

Load class 6KN 250mm Drain width

Dimension 300W x 500L x 25mm (t)



U33112

MG-INTERLACE-78

A15 Load class

Drain width 52 to 54mm

Dimension 78W x 610L x 21/25mm (t)



63117

INTERLACE-122

Load class A15

Drain width 92 to 100mm

122W x 498L x 22mm (t) Dimension



U32113

TG-INTERLACE-124

A15 Load class

Drain width 92 to 100mm

Dimension 124W x 500L x 22mm (t)



63118

INTERLACE-300

6KN Load class 250mm Drain width

Dimension 300W x 500L x 25mm (t)



63119

SQUARE-SLOTS-122

Load class A15 Drain width 80mm

Dimension 122W x 498L x 19mm (t)



U32116

TG-SQUARE-SLOTS-124LD

Load class

A15

Drain width 80 to 100mm

Dimension 124W x 500L x 19mm (t)



U32117

TG-SQUARE-SLOTS-124HD

Load class B125

72 to 82mm Drain width

Dimension 124W x 500L x 19/35mm (t)



63120

SQUARE-SLOTS-300

Load class A15 Drain width

250mm

Dimension 300W x 500L x 25mm (t)