



Easy Drain®
by ess

R-line | Polished | Ws 28/50 mm

Easy Drain R-line Waterstop is not just functional but also beautifully designed. This shower drain with subtle slope has a model for wall and floor installation. The R-line Waterstop is available in various standard lengths that can be shortened on-site. With its large pre-assembled sealing membrane (130x200 cm) it's easy to waterproof the complete shower floor while the Tile Adjustable Frame (TAF) system guarantees a 100% secure installation.

FEATURES

- Available lengths - 700 - 1200 mm
- Water Protection System - 10-year warranty
- Tile Adjustable Frame - Height adjustable 7 - 18 mm
- Certified - EN 1253
- Supplied as - Complete set
- Custom Length - Can be shortened on site
- Large sealing membrane (130x200 cm) - waterproofing the complete shower floor



Manufacturer

Easy Sanitary Solutions
Nijverheidsstraat 60 | 7575 BK Oldenzaal | The Netherlands
T. +31 (0)541 200 800 | F. +31 (0)541 200 899
info@esspost.com | www.easydrain.com

Contact

Easy Sanitary Solutions
Nijverheidsstraat 60 | 7575 BK Oldenzaal | The Netherlands
T. +31 (0)541 200 800 | F. +31 (0)541 200 899
sales@esspost.com | www.easydrain.com

Page 1 / 3

GENERAL

| | |
|---------------|---------------------------------|
| Serie | R-line |
| Name | R-line Polished Ws 28/50 mm |
| Model | Linear shower drain |
| Length (mm) | 700, 800, 900, 1000, 1200 |
| Product type | Complete |
| Application | Renovation, New construction |
| Certification | EN 1253, DIN 18534 |

INSTALLATION

| | |
|---|--|
| Substrate | Concrete / Sand Cement, Wooden floors, Lewis sheets, Synthetic, Concrete |
| Floor finish | Thin tiles, Tiles / Mosaic, Cast / screed, Glass Mosaic |
| Height adjustable feet | N.A. |
| Installation option | Floor |
| Outlet | Horizontal (Vertical outlet optional) |
| Connection (mm) | 50 (Global) / 56 (UK) |
| Min. installation depth (mm) (built-in set) | 69 (28 mm) / 85 (50 mm) |
| Min. installation depth (mm) (incl. grate) | 86 (28 mm) / 102 (50 mm) |

DRAINAGE

| | |
|---|-------------------------|
| Max. drainage capacity entrance (l/min) | 28 (28 mm) / 33 (50 mm) |
| Max. drainage capacity wall (l/min) | N.A. |
| Max. drainage capacity (l/min) | 28 (28 mm) / 33 (50 mm) |

BUILT-IN SET

| | |
|--------------------------------|--|
| Pre-assembled sealing membrane | Included |
| Siphon features | Cleanable, Pivotal & adjustable, Height adjustable |
| Water seal height (mm) | 28 / 50 |
| Outlet | Horizontal (Vertical outlet optional) |
| Material siphon | Polypropylene (PP) |

DESIGN

| | |
|-------------------------|-----------------------------|
| Grate finish | Polished stainless steel |
| Grate pattern | Slot |
| Grate width (mm) | 33 |
| Grate tile insert (mm) | N.A. |
| Adjustable grate | No |
| Frame type | TAF (Tile Adjustable Frame) |
| TAF Frame material | Stainless steel (304) |
| Design frame finish | Polished stainless steel |
| Frame width (mm) | 50 |
| Wheelchair accessible | Yes |
| Extension set available | N.A. |



Manufacturer

Easy Sanitary Solutions
 Nijverheidsstraat 60 | 7575 BK Oldenzaal | The Netherlands
 T. +31 (0)541 200 800 | F. +31 (0)541 200 899
 info@esspost.com | www.easydrain.com


Contact

Easy Sanitary Solutions
 Nijverheidsstraat 60 | 7575 BK Oldenzaal | The Netherlands
 T. +31 (0)541 200 800 | F. +31 (0)541 200 899
 sales@esspost.com | www.easydrain.com

ARTICLE CODE

| | | | |
|---------|---------------|--|--|
| 700 mm | R-LINE-700-P | | |
| 800 mm | R-LINE-800-P | | |
| 900 mm | R-LINE-900-P | | |
| 1000 mm | R-LINE-1000-P | | |
| 1200 mm | R-LINE-1200-P | | |
| | | | |

TECHNICAL DRAWINGS



Manufacturer

Easy Sanitary Solutions
 Nijverheidsstraat 60 | 7575 BK Oldenzaal | The Netherlands
 T. +31 (0)541 200 800 | F. +31 (0)541 200 899
 info@esspost.com | www.easydrain.com

Contact

Easy Sanitary Solutions
 Nijverheidsstraat 60 | 7575 BK Oldenzaal | The Netherlands
 T. +31 (0)541 200 800 | F. +31 (0)541 200 899
 sales@esspost.com | www.easydrain.com