

High Power SBA for 4400-5000MHz SBA4450XB

The SBA4450XB is a high power switched beam antenna that is particularly suitable for tactical communication applications (UHF band IV). The antenna beam can be switched by remote control to achieve optimal gain to the desired direction and to avoid interference from unwanted directions (LPI/LPD). The antenna provides up to 20 sharp beams with a minimum of 20-degree beamwidth to cover the full 360-degree horizontal area. In addition to these sharp beams the antenna can also provide wider beams.

- Great directivity with very low side lobe levels to undesired direction (LPI/LPD)
- Different beam modes available
- High power rating – 100 W



Product details*	
Frequency range	4400 - 5000 MHz
Polarization	Nominally vertical
Antenna type	Switched beam antenna
Radiation pattern	Available on request
Gain (typical)	15 dBi
3 dB beamwidth (typical)	25° (H-plane), 15° (H-plane)
Sidelobe level (typical)	-14 dB
VSWR	≤ 2.0
Nominal Impedance	50 Ω
Power rating	100 W (CW)
Power supply	12 VDC
Beam switching speed	< 35 μs (see information on Page 3)
Standard color	Black
Radiator	Selectable patch array element, 20 elements
Height	390 mm (including the mast mount adapter)
Diameter	270 mm
Weight	4.1 kg

Installation*	
RF connection	Female N-type connector
Power and control	Full Duplex RS-485 *
Mounting	Mast mount adapter for 40-60 mm masts included

* More information on request

Order number	
SBA4450XB	Antenna as described above

V0.2w
Date 06.03.2020

Page 1/1