

TECHNICAL DATA SHEET Gecko DECO

PRINTER TYPES





FLAME RETARDANT STANDARDS



DIN4102-B1, EN13501-1, NFPA701

APPLICATIONS

Interior wall decoration.



| PROPERTIES | TEST METHOD | RESULT | UNIT |
|------------------------|--|-----------------|---------------|
| Weight | | 365 ± 20 | gsm |
| Thickness | | 0.37 ± 0.02 | mm |
| Regular roll length | | 50 | meters |
| Max Width | DIN EN ISO 2286-1 | 5 | meters |
| Composition | Polyester yarn • PVC-free resin | | |
| Coating | Water-based • PVC-free • Phthalate free | | |
| Characteristics | Lightweight • Crease resistant • Stretchable • Perfect for high quality digital printing | | |
| Temperature Resistance | DIN 53361 | -40~+90 | ${\mathbb C}$ |

^{*}Test data is for reference only and may vary according to usage.*





No. 777 Fengguan Road, Fengjing Industrial Park, Jinshan District, Shanghai, China. Post Code:201501

TEL: +86-21-6463 2409 FAX: +86-21-6463 2157 EMAIL:info@goforkavalan.com WEB: www.goforkavalan.com



Greenhouse gas emissions of packaged PVC-free Kavalan banner (model Gecko DECO) for industrial application are 1.5 kgCO2e per 1 square meter (m2) unit. The calculation is based on the data collected from January 2020 to September 2020 from cradle to grave. SGS Report No. LCA21123-2