

### PRINTER TYPES



### FLAME RETARDANT STANDARDS



### APPLICATIONS

Mesh banners. Window curtains.



Image Courtesy of DIS Graphics UK (Molineux Stadium – Wolves F.C.)

PROPERTIES	TEST METHOD	RESULT	UNIT
Weight		180 ± 20	gsm
Thickness		0.35 ± 0.02	mm
Regular roll length		50	meters
Max Width	DIN EN ISO 2286-1	5	meters
Composition	Polyester yarn • PVC-free resin		
Coating	Water-based • PVC-free • Phthalate free		
Characteristics	Lightweight • Perfect for high quality digital printing		
Tensile Strength (W/F)	DIN 53354	200/166	Kg/5cm
Tear Resistance (W/F)	DIN 53363	35/30	Kg
Temperature Resistance	DIN 53361	-40~+90	°C

\*Test data is for reference only and may vary according to usage.\*



No. 777 Fengguan Road, Fengjing Industrial Park,  
 Jinshan District, Shanghai, China. Post Code:201501  
 TEL: +86-21-6463 2409  
 FAX: +86-21-6463 2157  
 EMAIL: info@goforkavalan.com  
 WEB : www.goforkavalan.com

Greenhouse gas emissions of packaged PVC-free Kavalan banner (model Spiderweb 300) for industrial application are **1.0 kgCO<sub>2</sub>e** per 1 square meter (m<sup>2</sup>) unit. The calculation is based on the data collected from January 2020 to September 2020 from cradle to grave.  
 SGS Report No. **LCA20123-5**