

TS-15 MINIBLOWER

Ideal for small demolition

Is ideal for the Elimination of Airborne Dust & Odour Emissions for both outdoor and indoor applications. Due to its small dimensions & handles & wheels kit it can pass through a standard doorway and is easy manoeuvrable.

The water supply is connected with a gardena brass adaptor and male 3/4" gas connection and power supply can come from mains or a generator.





MOBILE Handles and wheels for easy manoeuvrability



FAN 6 blades fan, complete with aluminium hub



COVERAGE Up to 15 m



WATER CONNECTION Gardena Brass adaptor male 3/4" gas thread





TS-15 MINIBLOWER



TECHNICAL DATA					
Electric motor	-	Single phase 230V 50Hz 2,2kW	Coverage (without wind)	m	15
Water pump	-	-	Nominal pressure	bar	1 up to 5
Electrical connection	-	2P+T plug 16A IP67	Water inlet filter	μm	300
Water connection	-	Gardena Brass adaptor male 3/4" gas thread	Tilting angle	-	0° to 45°
Protection rating	-	IP55	Dimensions	mm	1092 x 935 x 870h
Fan	n.	6 bladed	Dry weight	kg	97
Air flow	m³/h	90	Generator Required	kVA	5

Water consumption*					
1.0 bar	l/min	5.4			
1.5 bar	l/min	6.6			
2.0 bar	l/min	7.5			
2.5 bar	l/min	8.5			









