



LED TECHNOLOGY

2400 sqm
Area illuminated

PLUG-IN Line



Road
maintenance



Security



Outdoor
show



Special
events



Military
applications



Emergency



Operation: **POWER**

Inlet plug 32A - 230V

Outlet socket 32A - 230V

X-BOX
MANUAL

4x160W LED - 8M

T-ZERO^{PRO}

X-BOX MANUAL

4x160W LED - 8M

T-ZERO^{PRO}



FEATURES

- Telescopic galvanized sections
- 4x160W high efficiency LED heads
- On/off switch to light up the led heads
- Multi-directionally adjustable and tiltable by hands floodlights
- Guided main coiled cable to avoid damage during tower operation
- **Manual winch made from Al-ko with automatic brake system**
- Max height 8 meters
- Minimum height when complete close 2,5mt
- Simple, rugged machine design and layout
- Galvanized metalwork after 80 µm industrial powder coated
- **Compact dimensions for easy handling & transportability**
- Assembled on base
- 1150x1150mm base dimensions
- Sides forklift pockets
- Only one front opening door
- **Possibility to link to others towers**
(it will come complete with inlet plug and outlet socket)
- Small opening in the bottom of the front door to power the unit
- **Stackable**
- Complete with stabilizers
- 230V inlet plug
- 230V outlet socket

ZERO emissions	ZERO fuel costs	ZERO noise	MINIMAL service
STACKABLE	LINKABLE TOWERS	2400 sqm area illuminated	22 units per truck VERY COMPACT dimensions
Complete SILENCE on work time 8 HOURS A DAY 7 DAYS A WEEK			

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)
	1150x1150x2500 (LxWxH)		2350x2350x8000 (LxWxH)		556
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)
	Led	160W	4	65	2400
Mast	Lifting method	Max Height	Max Wind Speed	Safety brake	
	Manual	8 m	110 km/h	Mechanical and included in the winch	
Input&output	Inlet plug		Outlet socket		
	32A - 230V		32A - 230V		



TRIME[®]
Lighting Towers

Sales Dept. +39 0382 406 252
www.trime.it - info@trime.it