



**TRIME**<sup>®</sup>

Lighting Towers



LED TECHNOLOGY

**5000 sqm**

Area illuminated



Construction & work sites



Gas, oil & mining operations



Special events




Emergency



Military applications

**ENGINE POWERED** Line



Operation: **ENGINE POWERED**  
fuel tank capacity 80 litres  
Kubota Z482

**X-START**



4X320W - LED - 8,5M

## X-START 4X320W - LED - 8,5M



### FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8,5 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions for easy handling & transportability, up to 18 units per truck**
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)		
	1830x1370x2560 (LxWxH)		2320x2570x8500 (LxWxH)		706		
Floodlights	Type	Power (each)	Floodlights number	Illuminated area (sqm)			
	LED	320W	4	5000			
Mast	Lifting method	Max Height	Max Wind Speed	Rotation	Options		
	Manual	8,5 m	80 km/h	340°	Homologate road trailer		
Alternator	Model	Frequency (Hz)	Insulation class	Degree of protection	Single phase voltage	Auxiliary outlets	
	Synchronous	50	H	IP 23	3,5kVA - 230V	1 kVA	
Engine	Model	Fuel	r.p.m.	Tank capacity (l)	Consumption (l/h)	Running time	Noise level (dBA) at 7m
	Kubota Z482	Diesel	1500	80	0,55	145 h	65