


LED TECHNOLOGY

1600 sqm
Area illuminated

ENGINE POWERED Line



Operation: **ENGINE POWERED**
fuel tank capacity 81 litres
Kohler KD15/440

X-TR
2x150W LED-8M

X-TR 2X150W LED-8M



FEATURES

- **Toilette built-in**
- 6Kva Single-phase generator built-in
- **Fresh water level gauge**
- **Waste water level gauge**
- **Bathroom light**
- **Technical room light**
- Telescopic ladder for floodlights regulation
- **Road trailer**
- Removable ladder for easy and safe bathroom entrance
- 4 sides lifting eyes
- 2 Multi-directionally adjustable and tiltable by hands floodlights
- 8mt hydraulic vertical telescopic mast
- Galvanized metalworks
- 80 µm powder coating
- Forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- 4 drop down stabilizers

save money

RUNNING TIME
 81 litres tank
162 h
 Low fuel consumption

MINIMAL
 sevice

1600 sqm
 area illuminated

4 units
 per truck

General		Dimensions min (mm)			Dimensions max(mm)			Total weight (kg)			
		3446x2268x3054 (LxWxH)			3446x2268x8000 (LxWxH)			1770			
Floodlights		Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)					
		LED	150W	2	65	1600					
Mast		Lifting method			Max Height			Max Wind Speed			
		Hydraulic			8 m			110 km/h			
Generator		Model			Rated output		Rated frequency		Rated voltage		
		MeccAlte S20W 110/2			6 kVA		50 Hz		230 V		
Engine	Model	Cylinders	Fuel	r.p.m.	Fuel tank (l)	Consumption (l/h)	Running time (h)	Start	Displacement	Oil sump capacity (l)	Cooling system
	Kohler KD 15/440	1	Diesel	3000	81	0,55	162	Electric	442 cm ³	1,5	air
Water		Waste water tank capacity (l)		Fresh water tank capacity (l)		Cold water		Capacity (l)		Recirculating flush tank (l)	
		95		95		yes		36		160	