


05-443 and 05-444 PRIMALERT® Digital Area Monitors

Technical Data



The PRIMALERT Digital Area Monitors are designed for a wide range of gamma radiation area monitoring applications. Two self-contained configurations are available, each with an internal energy compensated GM detector (detection range in parentheses): 05-443 (0.1 mR/h to 1 R/h) and 05-444 (1 mR/h to 4 R/h). Both models are ac powered with an internal battery backup, have user-settable low and high alarms, and are available with an optional remote alarm for added security.

The versatile PRIMALERT Digital Area Monitors can be used in industrial applications, medical settings, or wherever there is a need to warn personnel of increasing radiation levels and/or to limit the accumulated exposure of personnel to gamma radiation.

Key features

- Simple installation and setup (calibration controls easily accessed through front panel)
- Anti-jam circuitry prevents erroneous readings at tube saturation
- LED digital display with Detector Fail indicator
- Programmable low and high alarm indicators, with an optional remote alarm available
- Data output/RS-232

Specifications

Indicated use	Radiation area monitoring
Internal GM detector range	05-443: 0.1 mR/hr to 1 R/hr; 05-444: 1 mR/hr to 4 R/hr
Display	4 digit LED display with 2 cm (0.8 in) character height; display range: 000.0 to 9999
Display units	Can be made to display in μ R/hr, mR/hr, R/h, μ Sv/h, mSv/h, Sv/h, cpm, cps and others
Linearity	Reading within $\pm 10\%$ of true value with detector connected
Response	Typically 3 seconds from 10% to 90% of final reading
Status (green light)	Indicates the instrument is functioning properly
Low alarm	Indicated by a yellow light and slow beep (1 per sec) audible tone (can be set at any point from 0.0 to 9999)
High alarm	Indicated by a red light and fast beep (4 per sec) audible tone (can be set at any point from 0.0 to 9999)
Detector fail	Red light and audible tone; > 68 dB at 2 ft indicates detector overload, no count from detector, or instrument failure
Low battery (yellow)	Indicates < 2 hours of battery power remaining
Calibration controls	Accessible from front of instrument (protective cover provided)
High voltage	Adjustable from 200 V to 2500 V
Threshold	Adjustable from 2 mV to 100 mV
Dead time	Adjustable to compensate for dead time of the detector and electronics (can be read on the display)
Overload	Senses detector saturation (indicated by display reading “-OL”)
Overrange	Indicates the radiation field being measured has exceeded the counting range of the instrument (indicated by display reading “----”)
Data output	9 pin connector providing 5 decade log output, RS-232 output, signal ground connection, FAIL and Alarm signals (current sink), and direct connection to battery and ground
Power requirements	95 V ac to 135 V ac (178 V ac to 240 V ac available), 50 Hz to 60 Hz single phase (< 100 mA), 6 V sealed lead acid rechargeable battery (built-in)
Battery life	Typically 48 hours in non-alarm condition, 12 hours in alarm condition
Battery charger	Battery is continuously trickle charged when instrument is connected to line power and turned on
Housing material	Aluminum housing with white polyurethane enamel paint
Temperature range	-20 °C to 50 °C (-4 °F to 122 °F). May be certified for operation from -40 °C to 65 °C (-40 °F to 150 °F)
Dimensions (WxDxH)	24.6 cm x 6.4 cm x 18.7 cm (9.7 in x 2.5 in x 7.4 in)
Weight	2.3 kg (6.5 lb)

Note: audible indicators can be configured as a single beep if desired.

Ordering information

Model numbers/descriptions

05-443 PRIMALERT Digital Area Monitor with internal energy compensated 0.1 mR/hr to 1 R/hr GM detector

05-443-2200 PRIMALERT Digital Area Monitor with internal energy compensated 1 μ Sv to 10 mSv/hr GM detector, 220 V ac operation

05-444 PRIMALERT Digital Area Monitor with internal energy

05-446 Remote Display

About Fluke Biomedical

Fluke Biomedical is the world’s leading manufacturer of quality biomedical test and simulation products. In addition, Fluke Biomedical provides the latest medical imaging and oncology quality-assurance solutions for regulatory compliance. Highly credentialed and equipped with a NVLAP Lab Code 200566-6 accredited laboratory, Fluke Biomedical also offers the best in quality and customer service for all your equipment calibration needs.

Today, biomedical personnel must meet the increasing regulatory pressures, higher quality standards, and rapid technological growth, while performing their work faster and more efficiently than ever. Fluke Biomedical provides a diverse range of software and hardware tools to meet today’s challenges.

Fluke Biomedical Regulatory Commitment

As a medical test device manufacturer, we recognize and follow certain quality standards and certifications when developing our products. We are ISO 9001 and ISO 13485 medical device certified and our products are:

- NIST Traceable and Calibrated
- UL, CSA, ETL Certified, where required
- NRC Compliant, where required

Fluke Biomedical.

Better products. More choices. One company.

Fluke Biomedical

6045 Cochran Road
Cleveland, OH 44139-3303 U.S.A.

Fluke Biomedical Europe

Science Park Eindhoven 5110
5692EC Son, The Netherlands

For more information, contact us:

In the U.S.A. (800) 850-4608 or
Fax (440) 349-2307
In Europe/M-East/Africa +31 40 267 5435 or
Fax +31 40 267 5436
From other countries +1 (440) 248-9300 or
Fax +1 (440) 349-2307
Email: sales@flukebiomedical.com
Web access: www.flukebiomedical.com

©2010-2013 Fluke Biomedical. Specifications subject to change without notice. All OEM company trademarks are implied. Printed in U.S.A. 12/2013 3670880C_EN

Modification of this document is not permitted without written permission from Fluke Corporation.