SHARKSKIN'



All construction professionals know the importance of a quality roof system. That is why so much research, time and effort goes into specifying and installing the right roofing product for every building.

The SHARKSKIN ULTRA® is designed to ensure that quality roof installations are not short-changed by inferior "old-technology" asphalt felts. The state of the art in recent underlayment advances, SHARKSKIN ULTRA® is 100% polypropylene product with a 12 month UV exposure rating. It is the toughest nailable polymer underlayment available.

Thermally stable with a melting point of 320° F, this high tensile strength reinforced product is approved as an alternate to inferior Type 15 and Type 30 roofing felts.

These days you can't afford to open yourself up to the potential liability of inferior roof underlayments. Give your customers the finest roofing system by starting with "The Ultimate Roof Underlayment". **Specify Sharkskin Ultra**®.

SHARKSKIN UNITED SHARKSKIN

Developed to exceed industry standards for long term moisture protection!

Code Compliance

- ICC-ES AC188, AC48 & ICBO AC08*
- ESR Report 1708
- BOCA
- SBCCI
- Florida Building Code FL#8097
- Miami/Dade HVHZ NOA 15-0421.10
- Exceeds ASTM D226

*Per tile roof installation instructions www.sharkskin.us / roll labels

Kirsch Building Products LLC
Tel: (805) 750-0084
Fax: (805) 526-1116
email: kirsch@sharkskin.us
www.sharkskin.us

1464 Madera Road Suite 387 Simi Valley, CA 93065

Patent # 6,308,482 American Owned and Operated 100% Recyclable 101-12004



The original Sharkskin Ultra... the most advanced synthetic underlayment on the market.





Benefits

High Tensile Strength

Provides a secondary water barrier if primary roof is blown off

Installs with 3/8" Roofing Nails

Does not require plastic caps

Nail Sealability

Provides long term nail sealabilty per ICC-ES AC48.

Easy to Mark

Use Crayon, holds a chalk line

Slip-Resistant

Even in wet or dusty conditions

Light Weight

Easy to lift, load, and work with 48" x 250' rolls – 10 SQS 45 lbs. per roll approx.

12 Month UV Exposure Rating

Will Not Rot

Will not rot, dry out or become brittle

No Expansion/Contraction

Material remains stable

White/Grey Surface

Stays cool to work on and keeps buildings cooler during construction

Will Not Wrinkle

Does not absorb moisture

Will Not Scar or Melt

NO Sticky Mess Withstands high temperatures

Eliminates Slip Sheet

Serves as a slip sheet beneath metal roofs

Visit Our Website! **www.sharkskin.us**



The first and most important step toward an integrated roof system.

